



**Search Parameters:**

[e-Catalog](#) > [Switches & Disconnects](#) > [Disconnect & Safety Switches](#)

**Switches & Disconnects, Disconnect & Safety Switches**

Product #: TC10324R

Short Description: 200A 2P DBL THR N3R 120/240V NONFUS

[Print This Page](#)

[Email This Page](#)

**SPECIFICATIONS**

Category	Double Throw
Voltage	120/240 AC
Amperage	200 A
Poles	2
Wires	3
Fusing	No Fuse
Enclosure	NEMA 3R (Outdoor)
Options	None
Height	30.16 in
Depth	8.47 in
Width	13.27 in
Weight	38.0 lb
Wire Range (Cu/Al)	6-250
240 Vac, NEC Std, 3-ph	15 hp
GSA Compliance	Yes
CSA Certified	No
UL Listed	Yes
GO Schedule	131A
List Price	\$1336



[View Larger](#)

**Publications/Resources**

[TC10324R](#)

**Additional Resources for Double Throw**

[Application and Technical](#)

[Brochures](#)

[Drawings-Outline and Dimensional](#)

[Installation and Instruction](#)

[Buy Log :2-21](#)

- Designed for outdoor rural dwellings and farm buildings to allow connection to a standby generator.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Suitable for use as transfer equipment in standby systems in accordance with Article 702 of the National Electrical Code.
- Non-fusible.
- 60/75°C conductor rating.
- Lockable handle in ON or OFF position.
- Galvanized steel construction.

