

# Catalog No. TDT3364R



**Description 200A 3P DBL THR SS N3R 600V FUSIBLE**

**UPC No 783164072440**

**Products > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Double Throw**

- Designed for commercial and industrial applications where safety, high performance and continuity of service are essential.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Suitable for use as transfer equipment in standby systems in accordance with Article 702 of the National Electrical Code.
- Fusible and non-fusible switches available (consult BuyLog for interrupt ratings).
- 60/75°C conductor rating.
- Full cover interlocks.

## Specifications

### Descriptors

Category	Double Throw
GO Schedule	SB

### Specifications

Voltage	600 AC
Amperage	200 A
Poles	3
Wires	3
Fusing	Fusible
Enclosure	NEMA 3R (Outdoor)
Options	None
Wire Range (Cu/Al)	6-250
240 Vac, NEC Std, 1-ph	15.0 hp
240 Vac, NEC Std, 3-ph	25.0 hp
240 Vac, Time Delay, 1-ph	15.0 hp
240 Vac, Time Delay, 3-ph	25.0 hp
480 Vac, NEC Std, 3-ph	50.0 hp
480 Vac, Time Delay, 1-ph	50.0 hp
480 Vac, Time Delay, 3-ph	125.0 hp
600 Vac, NEC Std, 1-ph	30.0 hp
600 Vac, NEC Std, 3-ph	60.0 hp
600 Vac, Time Delay, 1-ph	50.0 hp
600 Vac, Time Delay, 3-ph	150.0 hp
250 Vdc	40.0 hp
GSA Compliance	No

## Classifications

CSA Certified	No
UL Listed	Yes

## Dimensions

Height	51.4 in
Depth	8.8 in
Width	27.6 in
Weight	160.0 lb

## Publications

Title	Publication No.	Publication Type
<a href="#">3R, 200A - Safety Switches</a> 1 page outline drawing in .pdf format.	10103091-SH138	Drawings-Outline and Dimensional
<b>Additional Documentation:</b> Visit our <a href="#">Publication Library</a> to find technical documentation, time current curves, CSI Specifications and promotional literature.		