

**Search Parameters:**
[e-Catalog](#) > [Switches & Disconnects](#) > [Disconnect & Safety Switches](#)
**Switches & Disconnects, Disconnect & Safety Switches**

Product #: TH3365R

Short Description: 400A 3P HD SS N3R 600V FUSIBLE

 [Print This Page](#)
 [Email This Page](#)
**SPECIFICATIONS**

Category	Heavy Duty
Voltage	600 AC
Amperage	400 A
Poles	3
Wires	3
Fusing	Fusible
Enclosure	NEMA 3R (Outdoor)
Options	None
Height	53.19 in
Depth	8.34 in
Width	22.94 in
Weight	132.0 lb
Wire Range (Cu/Al)	(1) 2-600 or (2) 1/0-250
240 Vac, NEC Std, 3-ph	50 hp
240 Vac, Time Delay, 3-ph	125 hp
250 Vdc	50 hp
GSA Compliance	Yes
CSA Certified	Yes
UL Listed	Yes
GO Schedule	131
List Price	\$3414


 [View Larger](#)
**Publications/Resources**
[TH3365R](#)
**Additional Resources for Heavy Duty**
[Application and Technical Brochures](#)
[Drawings-Outline and Dimensional](#)
[BIM Files](#)
[Buy Log :2-11](#)

- Designed for commercial and industrial applications where safety, high performance and continuity of service are essential.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches.
- Meets or exceeds NEMA KS1 standard for enclosed switches - type HD.
- Fusible and non-fusible switches available (consult BuyLog for interrupt ratings).
- Quick-make, quick-break mechanism.
- 60/75°C conductor rating.
- Full cover interlocks.
- NEMA type 4X enclosure grade 304 stainless steel (catalog numbers with SS suffix).