

Search Parameters:
[e-Catalog](#) > [Switches & Disconnects](#) > [Disconnect & Safety Switches](#)
Switches & Disconnects, Disconnect & Safety Switches

 [Print This Page](#)
 [Email This Page](#)

Product #: TH4324R

Short Description: 200A 3P HD SS N3R 240V FUSIBLE SW.

SPECIFICATIONS

Category	Heavy Duty
Voltage	240 AC
Amperage	200 A
Poles	3
Wires	4
Fusing	Fusible
Enclosure	NEMA 3R (Outdoor)
Options	None
Height	31.31 in
Depth	5.11 in
Width	13.38 in
Weight	34.0 lb
Wire Range (Cu/Al)	2-250
240 Vac, NEC Std, 1-ph	15 hp
240 Vac, NEC Std, 3-ph	25 hp
240 Vac, Time Delay, 3-ph	60 hp
250 Vdc	40 hp
GSA Compliance	Yes
CSA Certified	Yes
UL Listed	Yes
GO Schedule	131
List Price	\$1130



 [View Larger](#)

Publications/Resources

[TH4324R](#)

Additional Resources for Heavy Duty

[Application and Technical](#)

[Brochures](#)

[Drawings-Outline and Dimensional](#)

[BIM Files](#)

[Buy Log :2-9](#)

- Designed for commercial and industrial applications where safety, high performance and continuity of service are essential.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches.
- Meets or exceeds NEMA KS1 standard for enclosed switches - type HD.
- Fusible and non-fusible switches available (consult BuyLog for interrupt ratings).
- Quick-make, quick-break mechanism.
- 60/75°C conductor rating.
- Full cover interlocks.
- NEMA type 4X enclosure grade 304 stainless steel (catalog numbers with SS suffix).