

## Catalog No. THN3361SS316



**Description 30A 3P HD N4X SS316 600V NONFUSE**

**UPC No 783164382358**

**Products > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty**

- Designed for commercial and industrial applications where safety, high performance and continuity of service are essential.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches.
- Meets or exceeds NEMA KS1 standard for enclosed switches - type HD.
- Fusible and non-fusible switches available (consult BuyLog for interrupt ratings).
- Quick-make, quick-break mechanism.
- 60/75°C conductor rating.
- Full cover interlocks.
- NEMA type 4X enclosure grade 316 stainless steel.

### Specifications

#### Descriptors

Category	Heavy Duty
GO Schedule	S1

#### Specifications

Voltage	600 AC
Amperage	30 A
Poles	3
Wires	3
Fusing	No Fuse
Enclosure	NEMA 4/4X (316 Stainless)
Options	None
Wire Range (Cu/Al)	14-6
240 Vac, NEC Std, 3-ph	10
480 Vac, NEC Std, 1-ph	7.5
480 Vac, NEC Std, 3-ph	20
600 Vac, NEC Std, 1-ph	10
600 Vac, NEC Std, 3-ph	30
125 Vdc	3
250 Vdc	5
GSA Compliance	Yes

#### Classifications

CSA Certified	Yes
---------------	-----

## Classifications

UL Listed	Yes
-----------	-----

## Dimensions

Height	11.3
Depth	4.9
Width	9.4
Weight	16

## Publications

Title	Publication No.	Publication Type
<a href="#">60A (incl. 316 Stainless) - Safety Switches</a> 1 page outline drawing in .pdf format.	10103091-SH109	Drawings-Outline and Dimensional
<b>Additional Documentation:</b> Visit our <a href="#">Publication Library</a> to find technical documentation, time current curves, CSI Specifications and promotional literature.		