

Accommodates waterproof splicing of #14 - #8 AWG UF copper wire.


- Connector set screws engage each wire securely for a solid splice.
- Minimum conductor size 14/2 with ground.
- Maximum conductor size 8/3 with ground.

Pkg Qty Description

• Rated at 600 V max.

HST-1300		1 kit	Underground UF Splice Kit	
Kit Contains:				
	Qty	Desc	cription	
	4 Screw Splice Connectors		Connectors	
	1	8" H	eavy-Wall	Polyolefin Heat-Shrink Tubing with Watertight





Butt Splice Kit (#8 - #2 AWG)

Used for waterproof installation or repair of #8 - #2 AWG copper cable.


- Easy to use.
- Seal with heat gun or torch.

Adhesive Liner

- Eliminates messy epoxies, tapes or mastics.
- Rated at 600 V max.

Part #			Pkg Qty	Description			
HSB-28		3	1 kit	Butt Splice Kit			
	Kit C	Kit Contains: Qty Description					
	1	Scre	w Splice Connectors				
	1		eavy-Wall Pesive Liner	olyolefin Heat-Shrink Tubing with Watertight			





Butt Splice Kit (#14 - #8 AWG)

Used for waterproof repair of well pipe cables and splices of stranded cable #14 - #8 AWG.

- Connector set screws engage each wire for a secure splice.
- · Assures safe and permanent connections.
- Rated at 600 V max.

Part #	Pkg Qty	Description	
HST-WP	1 kit	Butt Splice Connector Kit	
lan a			
Kit Contains:			



(ŲL)

Kit Contains:

Qty Description

- Screw Splice Connectors
- 4" Heavy-Wall Polyolefin Heat-Shrink Tubing with Watertight Adhesive Liner

