


# 11052 - FC16T9/D

### GE active spaces circline 40 watt T9 circline 1-pack

- 1.1 inch diameter T9 circline with 4-pin (g10q) base
- 6500K daylight appearance
- Bluish white light for super cool appearance
- · For use in high-activity areas throughout your home
- GE active spaces daylight circline fluorescent bulbs provide a cooler tone for an energetic environment. Use in
- rooms and spaces where cool, bluish light is desired
- Lasts 5.5 years based on 6 hours per day usage
- 16 inches long







### **CAUTIONS & WARNINGS**

#### Caution

- Lamp may shatter and cause injury if broken
- Wear safety glasses and gloves when handling lamp.
- Do not use excessive force when installing lamp.


#### Warning

Risk of Electric Shock

- Turn power off before inspection, installation or removal.

## **GRAPHS & CHARTS**

#### **Graphs\_Spectral Power Distribution**



Graphs\_Lamp Mortality

## **GENERAL CHARACTERISTICS**

Lamp Type Bulb Base Rated Life (NOM) Bulb Material Starting Temperature (MIN) Mercury Content (NOM) Picograms of Mercury (NOM) Primary Application Linear Fluorescent - Circular T9 4-Pin (G10q) 12000.0 h Lead glass 10.0 °C 7.0 mg 345.2 pg Full Wattage;Active Spaces

### **PHOTOMETRIC CHARACTERISTICS**

Initial Lumens (NOM)2250.0Mean Lumens (NOM)1690.0Nominal Initial Lumens per Watt56.25(NOM)Color Temperature (NOM)6500.0 KColor Rendering Index (CRI)75.0(NOM)Color Rendering Index (CRI)75.0

## **ELECTRICAL CHARACTERISTICS**

Wattage (NOM) 40.0 Open Circuit Voltage (instant 205 V @ 10 °C start ) Min @ Temperature Open Circuit Voltage (rapid 205 V @ 10 °C start) Min @ Temperature Cathode Resistance Ratio - Rh/ 4.25 Rc (MIN) Cathode Resistance Ratio - Rh/ 6.5 Rc (MAX) Current Crest Factor (MAX) 1.7

#### DIMENSIONS

Maximum Overall Length (MOL) (NOM) Nominal Length (NOM) Bulb Diameter (DIA) (MIN) Bulb Diameter (DIA) (MAX) Bulb Diameter (DIA) (NOM) Inside Diameter (MAX) Outside Bulb Diameter (MIN) Outside Bulb Diameter (MAX) Opposing Wall Inside Base (NOM) 16.000 in(406.4 mm) 16.000 in(406.4 mm)

1.030 in(26.2 mm) 1.220 in(31.0 mm) 1.125 in(28.6 mm) 13.690 in(347.7 mm) 15.500 in(393.7 mm) 16.000 in(406.4 mm) 13.690 in(347.7 mm)

## **PRODUCT INFORMATION**

Product Code Description ANSI Code Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC 11052 FC16T9/D 78901-ANSI-4034-1 Case 00043168110525 12 Unit 1 12

043168981231

