






GE
Lighting

11084 - FC8T9/KB

GE kitchen & bath circline 22 watt T9 circline 1-pack

- For use in kitchens and baths
- Food looks fresher & skin tones are more attractive
- Lasts up to 8 years!
- 1.1 inch diameter T9 circline with 4-pin (g10q) base
- Lasts 5.5 years based on 6 hours per day usage
- 3000K warm white light appearance
- For use in kitchens, bathrooms, and living areas
- GE kitchen & bath circline fluorescent bulbs deliver a warmer tone to create a comfortable and inviting atmosphere. These warm white bulbs are best for living areas throughout your home, hotels, commercial restrooms, reception areas and food preparation
- Warm, inviting light that complements any decor



CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
 - Wear safety glasses and gloves when handling lamp.
 - Do not use excessive force when installing lamp.

Warning

- Risk of Electric Shock
 - Turn power off before inspection, installation or removal.
 - Avoid direct water/liquid contact.

*Five year life based on rated life at 6 hours/day.

GRAPHS & CHARTS

Graphs_Lamp Mortality

GENERAL CHARACTERISTICS

Lamp Type	Linear Fluorescent - Circular
Bulb	T9
Base	4-Pin (G10q)
Rated Life (NOM)	12000.0 h
Bulb Material	Lead glass
Starting Temperature (MIN)	10.0 °C
Mercury Content (NOM)	7.0 mg
Picograms of Mercury (NOM)	520.8 pg
Primary Application	Full Wattage;Kitchen & Bath

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	1400.0
Mean Lumens (NOM)	1120.0
Nominal Initial Lumens per Watt (NOM)	63.63636
Color Temperature (NOM)	3000.0 K
Color Rendering Index (CRI) (NOM)	82.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	22.0
Open Circuit Voltage (instant start) Min @ Temperature	180 V @ 10 °C
Open Circuit Voltage (rapid start) Min @ Temperature	230 V @ 10 °C
Cathode Resistance Ratio - Rh/Rc (MIN)	4.25
Cathode Resistance Ratio - Rh/Rc (MAX)	6.5
Current Crest Factor (MAX)	1.7

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	8.250 in(209.5 mm)
Nominal Length (NOM)	8.250 in(209.5 mm)
Bulb Diameter (DIA) (MIN)	1.030 in(26.2 mm)
Bulb Diameter (DIA) (MAX)	1.220 in(31.0 mm)
Bulb Diameter (DIA) (NOM)	1.125 in(28.6 mm)
Inside Diameter (MAX)	6.190 in(157.2 mm)
Outside Bulb Diameter (MIN)	8.000 in(203.2 mm)
Outside Bulb Diameter (MAX)	8.500 in(215.9 mm)
Opposing Wall Inside Base (NOM)	6.130 in(155.7 mm)

PRODUCT INFORMATION

Product Code	11084
Description	FC8T9/KB
ANSI Code	78901-ANSI-4031-1
Standard Package	Case
Standard Package GTIN	10043168110843
Standard Package Quantity	6
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	6
UPC	043168110846

