




GE
Lighting

15867 - F39BXSPX35RS10PK

GE Biax® T5 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse




CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
 - Remove and install by grasping only plastic portion of the lamp.

GRAPHS & CHARTS

Graphs_Spectral Power Distribution



NOTES

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life
- Life ratings for the F18BX preheat lamps are based on operating the lamp at 3 hrs per start on a preheat type circuit. Operation on rapid start and instant start ballasts is not recommended. Life ratings for all lamps are based on operating the lamp at 3 hrs per start on a rapid start type ballast. Life rating on a preheat or instant start ballast is 25% lower than other Rapid Start High Lumen Biax.

GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Plug-In
Bulb	T5
Base	4-Pin (2G11)
Equivalent Wattage	180.0 W
Rated Life	12000.0 hrs
Starting Temperature (MIN)	10.0 °C
LEED-EB MR Credit	133 picograms Hg per mean lumen hour
Primary Application	Facilities;Retail Display;Hospitality;Office;Restaurant;W

PHOTOMETRIC CHARACTERISTICS

Initial Lumens	2850.0
Mean Lumens	2510.0
Nominal Initial Lumens per Watt	73
Color Temperature	3500.0 K
Color Rendering Index (CRI)	82.0

ELECTRICAL CHARACTERISTICS

Wattage	39.0
Voltage	107.0
Lamp Current	0.428 A
Current Crest Factor (MAX)	1.7

DIMENSIONS

Maximum Overall Length (MOL)	16.5000 in(419.1 mm)
Nominal Length	16.500 in(419.1 mm)

PRODUCT INFORMATION

Product Code	15867
Description	F39BXSPX35RS10PK
ANSI Code	60901-IEC-4236-1
Standard Package	Master
Standard Package GTIN	10043168158678
Standard Package Quantity	40
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	40
UPC	043168158671