

# 20833 - GE ConstantColor® Precise™ MR16 Q50MR16/C/FL40 **Product Photo**



### **GENERAL CHARACTERISTICS**

Base Description Base Type Filament Rated Life Hours-nominal Lamp Enclosure Type Product Technology Base **Bulb Shape** 

#### PHOTOMETRIC CHARACTERISTICS

Beam Spread Center Beam Candle Pwr Candela Initial Lumens-nominal **Color Temperature** 

## **PRODUCT INFORMATION**

Product Code	20833
Description	Q50MR16/C/FL40
Alternative Unit Of Measure	EACH
Standard Package Quantity	20
Ean UPC	043168994262
Standard Package GTIN	00043168994262
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	20
Sales Unit	Each
UCC	043168208338
Alternative Unit Of Measure	CASE
DIMENSIONS	

# Diameter

### **ELECTRICAL CHARACTERISTICS**

Input Voltage [nom]	12 V
Rated power (Watts)	50 W

## **CAUTIONS & WARNINGS**

#### Caution

Lamp may shatter and cause injury if broken

Dispose of lamp in a closed container.

Do not use lamp if outer glass is scratched or broken.

## Warning

Risk of Burn

Allow lamp/fixture to cool before handling.

Turn power off before installing lamp.

#### Risk of Fire

Keep combustible materials away from lamp.

Use in enclosed fixture rated for this product -- see instructions.

Pressurized lamp--unexpected rupture may cause injury, fire, or property damage

Do not touch glass with bare hands.

Do not use lamp if outer glass is scratched or broken.

Use eye protection when handling lamp.

Use in enclosed fixture rated for this product.

2-Pin Pin/Plug-In C-6 6000 h Open or enclosed fixtures Halogen GX5.3 **MR16** 

40 deg 1700 cd 800 lm 3050 K

2.0 in