



ProLume T3 Mini-Spirals

Halco
LIGHTING TECHNOLOGIES

Energy Efficient:

- Maximum light distribution achieved through compact design
- Save up to 80% in energy costs compared to incandescent lamps
- Tri-phosphor coating enhances lumen efficacy and color rendering, 82 CRI

Specifications:

- Dimmable 13, 18 and 23 watt
- 3-Way 13/20/25 watts available in 2700 and 4100K
- Available in 11, 13, 15, 18, 20, 23, 26, 27, 32 and 42 watts
- 2700, 3500, 4100, 5000 and 6500K color temperatures available
- Colors available in 11 and 15 watt
- Black-Light Blue available in 15 watt
- GU24 18, 23 and 26 watts available in 2700, 3500, 4100 and 5000K; GU24 13 watt available in 2700K
- E26 base and GU24 base
- Electronic instant start ballast
- 120 volt, 60Hz
- Minimum starting temperature -10°F
- Nickel-plated brass base
- 8,000-12,000 Hours Average Rated Life

- » Saves energy
- » Low maintenance
- » Compact design

Markets:

- Residential
- Commercial

Applications:

- Table lamps
- Down lighting
- General lighting

where there's light, there's halco®

Contact your account representative at 800.677.3334 for pricing, orders and technical support.

Visit us at halcolighting.com

ProLume T3 Mini-Spirals

Catalog Number: _____ Type: _____
 Project: _____
 Comments: _____ Date: _____
 Prepared By: _____

COMPACTS

Bulb Type	Watts	Base	Product #	Product Code	Description	Pkg/ Qty	Color Temp	CRI	Initial Lumens	Incandescent Equivalent	Avg Rated Life	MOL (Inches)
T3 MINI-SPIRALS												
T3	11	Med.	109240	CFL11/27	Warm White	10/50	2700	82	700	40	12000	4.29"
T3	11	Med.	109242	CFL11/41	Cool White	10/50	4100	82	700	40	12000	4.29"
T3	11	Med.	109244	CFL11/50	Natural White	10/50	5000	82	700	40	12000	4.29"
T3	11	Med.	109224	CFL11/BLU	Blue	10/50	-	-	-	40	8000	4.29"
T3	11	Med.	109226	CFL11/GRN	Green	10/50	-	-	-	40	8000	4.29"
T3	11	Med.	109220	CFL11/RED	Red	10/50	-	-	-	40	8000	4.29"
T3	11	Med.	109222	CFL11/YEL	Yellow	10/50	-	-	-	40	8000	4.29"
T3	13	Med.	45101	*CFL13/27	Warm White	10/50	2700	82	900	60	10000	4.41"
T3	13	Med.	45103	*CFL13/35	White	10/50	3500	82	900	60	10000	4.41"
T3	13	Med.	45104	*CFL13/41	Cool White	10/50	4100	82	900	60	10000	4.41"
T3	13	Med.	45105	*CFL13/50	Natural White	10/50	5000	82	900	60	10000	4.41"
T3	13	Med.	45107	*CFL13/65	Daylight	10/50	6500	82	850	60	10000	4.41"
T3	13	GU24	46544	CFL13/27/GU24/DIM	Warm White Dimmable	10/60	2700	82	800	60	10000	4.00"
T3	15	Med.	109252	CFL15/27	Warm White	10/50	2700	82	950	60	10000	4.94"
T3	15	Med.	46330	CFL15/27/DIM	Warm White Dimmable	10/60	2700	82	950	60	10000	4.92"
T3	15	Med.	109330	CFL15/35	White	10/50	3500	82	950	60	10000	4.94"
T3	15	Med.	109261	CFL15/41	Cool White	10/50	4100	82	950	60	10000	4.94"
T3	15	Med.	109272	CFL15/50	Natural White	10/50	5000	82	950	60	10000	4.94"
T3	15	Med.	109270	CFL15/BLB	Blacklight-Blue	10/20	-	-	-	60	12000	4.94"
T3	15	Med.	109288	CFL15/YEL	Yellow	10/50	-	-	-	60	12000	4.94"
T3	18	Med.	45120	*CFL18/27	Warm White	10/50	2700	82	1200	75	12000	5.24"
T3	18	Med.	45122	*CFL18/35	White	10/50	3500	82	1200	75	12000	5.24"
T3	18	Med.	45123	*CFL18/41	Cool White	10/50	4100	82	1200	75	12000	5.24"
T3	18	Med.	45124	*CFL18/50	Natural White	10/50	5000	82	1200	75	12000	5.24"
T3	18	GU24	46546	CFL18/27/GU24/DIM	Warm White Dimmable	10/50	2700	82	1200	75	10000	4.40"
T3	20	Med.	109254	CFL20/27	Warm White	10/50	2700	82	1250	75	12000	5.25"
T3	20	Med.	109263	CFL20/41	Cool White	10/50	4100	82	1250	75	12000	5.25"
T3	20	Med.	109274	CFL20/50	Natural White	10/50	5000	82	1250	75	12000	5.25"
T3	23	Med.	45250	*CFL23/27	Warm White	10/50	2700	82	1600	100	10000	5.04"
T3	23	Med.	46334	*CFL23/27/DIM	Warm White Dimmable	10/50	2700	82	1600	100	10000	5.59"
T3	23	Med.	45252	*CFL23/35	White	10/50	3500	82	1600	100	10000	5.04"
T3	23	Med.	45253	*CFL23/41	Cool White	10/50	4100	82	1600	100	10000	5.04"
T3	23	Med.	45254	*CFL23/50	Natural White	10/50	5000	82	1600	100	10000	5.04"
T3	23	GU24	46548	CFL23/27/GU24/DIM	Warm White Dimmable	10/50	2700	82	1600	100	10000	4.73"
T3	13/20/25	Med.	45720	CFL25/27/3WAY	Warm White 3-Way	10/50	2700	82	900/1200/1600	30/70/100	8000	6.13"
T3	13/20/25	Med.	45721	CFL25/41/3WAY	Cool White 3-Way	10/50	4100	82	900/1200/1600	30/70/100	8000	6.13"
T3	26	GU24	46528	*CFL26/27/GU24	Warm White	10/50	2700	82	1750	100	10000	5.20"
T3	26	GU24	46531	*CFL26/35/GU24	White	10/50	3500	82	1750	100	10000	5.20"
T3	26	GU24	46529	*CFL26/41/GU24	Cool White	10/50	4100	82	1750	100	10000	5.20"
T3	26	GU24	46530	*CFL26/50/GU24	Natural White	10/50	5000	82	1750	100	10000	5.20"
T3	27	Med.	109310	CFL27/27	Warm White	10/50	2700	82	1900	100	10000	5.44"
T3	27	Med.	45255	CFL27/35	White	10/50	3500	82	1850	100	10000	5.44"
T3	27	Med.	109312	CFL27/41	Cool White	10/50	4100	82	1850	100	10000	5.44"
T3	27	Med.	109314	CFL27/50	Natural White	10/50	5000	82	1750	100	10000	5.44"

ProLume T3 Mini-Spirals

Catalog Number: _____ Type: _____
 Project: _____
 Comments: _____ Date: _____
 Prepared By: _____

COMPACTS

Bulb Type	Watts	Base	Product #	Product Code	Description	Pkg/ Qty	Color Temp	CRI	Initial Lumens	Incandescent Equivalent	Avg Rated Life	MOL (Inches)
T3	32	Med.	109316	CFL32/27	Warm White	10/50	2700	82	2250	125	8000	5.56"
T3	32	Med.	109318	CFL32/41	Cool White	10/50	4100	82	2200	125	8000	5.56"
T3	32	Med.	109306	CFL32/50	Natural White	10/50	5000	82	2200	125	8000	5.56"
T3	42	Med.	109328	CFL42/27	Warm White	6/24	2700	82	2900	150	12000	7.06"
T3	42	Med.	109336	CFL42/41	Cool White	6/24	4100	82	2800	150	12000	7.06"
T3	42	Med.	109338	CFL42/50	Natural White	6/24	5000	82	2800	150	12000	7.06"

* UL approved for totally enclosed fixtures with a max ballast case temperature of 90°C for GU24 base lamps, 75°C for medium base lamps.

 Hg—LAMP CONTAINS MERCURY, MANAGE IN ACCORD WITH DISPOSAL LAWS.

Visit www.lamprecycle.org for disposal information for your state or local government.



CAUTION: Non-dimmable lamps should not be used on dimming circuits, timing devices, photo sensors or occupancy sensors.

This device is not intended for use with emergency exit fixtures.

This device complies with Part 18 of the FCC Rules. This product may cause interference with radio equipment and should not be installed near maritime safety communications equipment, ships at sea or other critical navigation or communications equipment operating between 0.45-30 MHz.

WARRANTY - Commercial/Industrial: Dimmable lamps are warranted for 2 years from date of purchase based on 3 hours of use per day.

Non-dimmable lamps are warranted for 2 years from date of purchase based on 10 hours of use per day.



Atlanta | Carlstadt | Cleveland | Los Angeles | Houston | Phoenix