

SM1BK75MT



Article Number: 800-00004

Self-Extinguishing Flexiform Grommet, Panel Thickness .03937"-.07874, PVC, Black, 246.1ft/pkg



Base Data

Local Order Number SM1BK75MT

Type SM1

Color Black (BK)

Features and Benefits

- Fits in holes of all shapes and sizes without the aid of tools or adhesives, making installation easy.
- Easily cut to the right length with scissors, thus reducing stock and eliminating waste.
- Can be used on any type of material including wood, steel, aluminum, plexiglass and glass, ensuring flexibility of application.

Product Description EdgeGuard is used to cover panel edging to protect cables, prevent chafing and provide an attractive finish. The EdgeGuard is manufactured from a flexible PVC compound ensuring ease of use.

Short Description Self-Extinguishing Flexiform Grommet, Panel Thickness .03937"-.07874, PVC, Black, 246.1ft/pkg

Product Dimensions

Length L (imperial) 246.1 ft

Length L (metric) 75 m

Width W (imperial) 0.1969 "

Width W (metric) 5.0 mm

Width W2 (imperial) 0.03937 "

Width W2 (metric) 1.0 mm

Width W3 (imperial) 0.07 "

Width W3 (metric) 1.8 mm

Width W4 (imperial) 0.165 "

Width W4 (metric) 4.2 mm

Height H (imperial) 0.248 "

Height H (metric) 6.3 mm

Height H2 (imperial) 0.192 "

Height H2 (metric) 4.9 mm

Panel Thickness max. (imperial) 0.08 "

Panel Thickness max. (metric) 2.00 mm

Panel Thickness min. (imperial) 0.04 "

Panel Thickness min. (metric) 1.00 mm

Logistics and Packaging

Quantity per roll

Package Quantity (imperial) 246.1 ft

Package Quantity 75 m

Carton Quantity 75 Meter
Reel Length (metric) 75 m
Reel Length (imperial) 246.1 ft
Weight (Metric) 2.56 kg

Material and Specifications

Material Polyvinylchloride (PVC)
Material Shortcut PVC
Flammability UL94 HB
Operating Temperature -85 °F to +221 °F (-65 °C to +105 °C)
ROHS Conformity Yes