

## Thermostats

- > Programmable Thermostats
- > Non-Programmable Thermostats
- > Thermostat Parts and Accessories

- Whole House Air Quality
- HVAC Zoning
- Residential Combustion
- EnviraCOM
- Communications
- Water Control
- Training Materials & Product Literature

## Quick Links

- Tradeline Catalog Printed Version (114 MB)
- Tradeline Catalog CD-ROM version (50 MB)

## Locators

- ACI Contractor
- Residential Contractor
- Distributor

## Environmental & Combustion Controls



> Programmable Thermostats > Line Volt PRO™ > TL8230

### TL8230A1003

Digital Programmable Double Pole Line Voltage Thermostat for electric baseboards, convectors and fan forced heaters (resistive rated loads).

- Locate Distributors
- Product Specifications
- Literature and Documents



### Overview

The LineVoltPRO™ programmable thermostat provides electronic control of 208/240 Vac resistive rated electric baseboard heaters, radiant ceiling heat, radiant floor heat, convectors and fan forced heaters.

### Features

- 7 day programmable - maintain the pre-set program schedule for up to 20% energy savings, or modify the schedule to fit your lifestyle.
- Electronic temperature control - precision of  $\pm 1^\circ$  F saves up to an additional 10% on heating bills.
- Large, clear, backlit display - easy to read in various lighting conditions.
- Soundproofed for quiet operation - reduces the clicking noise commonly heard with conventional thermostats.
- On/Off switch allows you to turn the thermostat off at the end of the heating season.
- Early start - ensures programmed temperature is reached by programmed time.
- Heating indicator - at a glance confirmation that the heat is on.
- Maintenance free - no batteries required.
- 5-year limited warranty.

### Product Specifications

[→ Back To Top](#)

Application	Electric baseboards, convectors and fan forced heaters (resistive rated loads).
Programmability	7 Day Program
Color	Premier White®
Switching Action	DPST
Dimensions (in.)	4 7/8 in. high x 2 3/4 in. wide x 7/8 in. deep

### Welcome

[Login to My Account](#) →

[→ New User Registration](#)

[→ Find Quote](#)

### Product Search



### Cross Reference Search



### Search



[→ Advanced Search](#)

### Literature / Image Search

All Literature ▾

Model / Part Number ▾




Dimensions (mm)	124 mm high x 70 mm wide x 23 mm deep
Mounting	Vertical Mount
Electrical Ratings	15 Amps Max; 3600 Watts at 240 VAC, 3120 Watts at 208 VAC
Frequency	50/60 Hz
Electrical Connections	5.5 in. (140mm) tinned copper lead wires
Operating Temperature Range (F)	32F to 122 F
Operating Temperature Range (C)	0 C to 50 C
Setting Temperature Range (F)	40 F to 86 F
Setting Temperature Range (C)	5 C to 30 C
Stages	1 Heat
Sensor Element	Thermistor
Approvals, Underwriters Laboratories Inc	UL Listed 9R12, File Number: E183695
Approvals, Canadian Standards Association	cCSAus, File Number: LR76030
Display Size	2.67 sq. in.
Voltage	208/240 Vac

#### Literature and other Resources Download [→ Back To Top](#)

TL8230A1003 LineVoltPRO 8000 7-Day Programmable Electric Heat Thermostat  
 Programmable Thermostat(User Guide - PDF)  
 Termostato programable - Spanish(User Guide - PDF)  
 Programmable Thermostat(Installation and User Guide - PDF)  
 Programmable Thermostat(Installation and User Guide - PDF)  
 Power Base, English, French, Spanish(Installation Guide - PDF)

**Download** 

[Terms & Conditions](#) | 
 [Privacy Statement](#) | 
 [Site Map](#) | 
 [Advanced Search](#)

Choose Your Region/Country **United States English** 

v1.0.2844

© Copyright Honeywell International Inc 2004-2007