

Ceiling and Wall Mount Occupancy Sensor Accessories

SENSOR ACCESSORIES

PROJECT INFORMATION

Project Name _____

Catalog No. _____

Date _____

ACAK — Acoustic Ceiling Mounting Kit

For ceiling and wall mount sensors used with acoustic ceiling tile. ACAK uses integral cutting teeth for quicker installation. Color: White.

LMRA — LightOWL® Mud Ring ADAPTER

A LightOWL goof ring for covering oversized holes. Color: White.

HCRA — Hard Ceiling Raceway Adapter

For OMNI® sensors. The HCRA is compatible with Hubbell and Wiremold raceway. The HCRA has knockout raceway holes for quick and clean installation. Color: White.

OPE – OMNI Protective Enclosure

The OPE is a NEMA Type 4X enclosure specifically designed for use with HCS's OMNIIR ceiling mount occupancy sensor. Designed to provide protection from foreign materials and water, the enclosure is acceptable for use in a variety of environments including applications in the pharmaceutical and food pre-preparation industries. Size: 6.5" dia., 2" height. Color: White.

WGWS – Wall mount wire guard for wall switches, 6.25"H x 4.0"W x 2.25"D

WGLO – Wall mount wire guard for LightOWL sensors, 7.0"H x 5.75"W x 4.5"D

WGOMNI – Ceiling mount guard for OMNI sensors, 7.0"W x 3.25"D (circular guard) Wire guards are heavy-duty coated wire guards for sensors to protect from destructive strikes. Mounting clips are included. Color: White.

Ordering Information

--

COLOR

ACAK Acoustic Ceiling Mount Kit

LMRA LightOWL Mud Ring Adapter

HCRA Hard Ceiling Adapter

OPE OMNI Protective Enclosure

WGWS Wire Guard for Wall Switches

WGLO Wire Guard for LightOWL sensors

WGOMNI Wire Guard for OMNI Sensors



ACAK
(Shown with LightOWL
mounting arm.)



LMRA



OPE



HCRA



WGWS



WGOMNI



WGLO



HUBBELL
Control Solutions