S9	Cat.#		
SERIES	Job	Туре	
VANDAL RESISTANT FIXTUR	RES		Approvals
 APPLICATIONS Ceiling/canopy lighting. Sat garage, entrance canopies SPECIFICATIONS Die cast aluminum housing Vandal resistant prismatic Bronze powder paint finish Medium base or compact finish Typical mounting height rat LISTINGS S9 Series 	s, stairwells, building eav g with 1/2" conduit hubs polycarbonate refractor n on H.I.D. units fluorescent lamps include	es	PRODUCT IMAGE(S)
Listed to UL1598 for use in Center pin torx screws are		r ceiling mount	S9 H.I.D. DIMENSIONS
Listed to UL1598 for use ir Center pin torx screws are		r ceiling mount	
Listed to UL1598 for use in Center pin torx screws are CERTIFICATIONS/LISTINGS c	standard		

ORDERING INFORMATION

Catalog Number ¹	Description	Voltage	Finish	Weight Ibs. (kg)		
Wet Location - Ceiling / Wall Mount Compact S9 – 9 inch Square						
S9-70H	-70H 70w PSMH		Bronze	10 (4.5)		

REPLACEMENT PARTS

Catalog Number	Description	
SM009-LENS	Refractor only for S9 units	