



Hubbell Lighting's ExpressLine family
Value & Service for you and your customers!



ExpressLine by Hubbell Lighting

The name Hubbell has long been associated with quality products sold through the Electrical Distribution Channel. Our Outdoor Lighting products are recognized and readily accepted by contractors and universally recognized as leading in quality and value by specifiers. Hubbell Outdoor and Industrial Lighting continues this tradition of quality, strengthening our support of this partnership today.

This new product offering, *ExpressLine*, expands our product range and price points, increasing partnership opportunities to sell Hubbell to your electrical contractors. This new family contains twenty-one product series providing solutions to the lighting challenges brought to you each day. The merchandising cartons are designed to help both you and your contractor quickly select the right fixture for each task.

ExpressLine is just one part of the complete lighting package your Hubbell representative has to service your needs.





FLOODLIGHTING



Facade Flood

Designed for close setbacks from walls, signs, or small areas. Wide uniform beam covers area four times the setback distance. Cast aluminum housing, polycarbonate door, tempered glass lens, tool-free entry, 1/2" cast aluminum swivel knuckle, dark bronze finish. For use in wet locations. Lamp included. 0.6 EPA.

Catalog Numbe		
Caraioo Niiimbe		

F050H1	50 watt MH, 120V	8 lbs
F070H1	70 watt MH, 120V	9 lbs
F100H1	100 watt MH, 120V	10 lbs
F070S1	70 watt HPS, 120V	7 lbs
F150S1	150 watt HPS, 120V	8 lbs



Microliter® Floodlight

Medium beam flood for setbacks of six feet or more. Beam coverage is two times setback distance. Cast aluminum housing and door. Twin-screw closure with HubbellGard® treated hardware. Tempered glass lens, rotatable parabolic reflector system for best beam utilization. Large, 1/2" cast aluminum swivel knuckle, dark bronze textured finish. For use in wet locations. Lamp included. 0.7 EPA

			m	

MIC0100H358	100 watt MH, 120, 208, 240, 277V	13 lbs
MIC0175H358	175 watt MH, 120, 208, 240, 277V	14 lbs
MIC0150S258	150 watt HPS, 120, 208, 240, 277V	14 lbs
MIC0150S651	150 watt HPS, 120V	10 lbs



Miniliter® IV Wide Flood

Compact, 400 watt size flood. Very wide beam with uniform distribution. Beam coverage is four times setback distance. Cast aluminum housing and door. Tool-free lens/door access. Tempered glass lens, steel mounting yoke, dark bronze textured finish. For use in wet locations. Lamp included, 1.4 EPA.

Catalog Number

MHSY250H4681 250 watt MH, 120, 208, 240, 277V	22 lbs
MHSY400H4681 400 watt MH, 120, 208, 240, 277V	26 lbs
MHSY250S4681 250 watt HPS, 120, 208, 240, 277V	24 lbs
MHSY400S4681 400 watt HPS, 120, 208, 240, 277V	28 lbs



Quartz Floodlights

A wide range of white light, instant-on floods. Soft, uniform beam with coverage of two to three times setback distance. Cast aluminum housing and door. Single screw closure for weather-tight gasket seal. 1/2" cast aluminum swivel knuckle mounting. Bronze or white powder coat finish. For use in wet locations. Lamp included. QD units have built-in protective cast door guard.

Catalog Number

QD150B	150 watt, 120V, bronze	1.4 lbs
QD150W	150 watt, 120V, white	1.4 lbs
QD300B	300 watt, 120V, bronze	2.4 lbs
QD300W	300 watt, 120V, white	2.4 lbs
Q500B	500 watt, 120V, bronze	2.7 lbs
Q500W	500 watt, 120V, white	2.7 lbs

<u>.amp</u> Holders



Lampholders

Cast aluminum units with protective powder paint finish. A variety of unshielded, shielded, and deeply shielded designs for various application requirements. 1/2" cast aluminum swivel knuckle mounting. For use in wet locations. Universal aiming capability. Use PAR lamps outdoors (309 Series can use PAR or R lamps outdoors).

Catalog Number

Unshielded, 150 watt max., 120V bronze	.5 lbs
Shielded, 150 watt max., 120V bronze	1.25 lbs
Shielded, 150 watt max., 120V white	1.25 lbs
Deep shielded, 150 watt max., 120V bronze	3 lbs
	Shielded, 150 watt max., 120V bronze Shielded, 150 watt max., 120V white

309-M54ML Deep shielded, 150 watt max., 120V white 3 lbs

MOTION SENSORS



Motion Sensors

Molded bronze housing with double joint, 1/2" mounting stem. Passive infrared detection over 90° coverage area out to 50 feet. 500 watt incandescent switching capacity. Test mode, sensitivity, and burning time duration controls. Sensor consumes 5.4 watts. Internal components protected against moisture for long, reliable life.

Catalog Number

ZS1 Sensor only, 500 watt incand. capacity, 120V bronze 1.5 lbsZS2 Sensor, twin 150 watt lampholders.

box and cover, 120V bronze 4.3 lbs

WALLPACKS



Perimeter Wallpack

Polycarbonate front provides wide lateral spread and vandal resistance. Lateral coverage is five times the typical 6-10' mounting height. Molded-in bronze finish. Photocontrol units provide dusk-to-dawn energy management. Cast aluminum back housing provides solid mounting to wall or recessed wiring boxes. 1/2" bottom conduit knockout allows surface conduit wiring. For use in wet locations. Lamp included.

Cata		

NRG301B-PC	50 watt HPS, 120V, photocontrol, bronze 5 lbs
NRG307B-PC	70 watt HPS, 120V, photocontrol, bronze 5 lbs
NRG304B-PC	42 watt FLU, 120V, photocontrol, bronze 6 lbs



Compact Refractor Wallpack

Cast aluminum housing and door with glass refractor on metal halide units. Cast aluminum housing and polycarbonate refractor on vandal-resistant HPS units. Coverage is four times the 8-12' typical mounting height. 1/2" conduit hubs allow surface wiring and field installations of photocontrols. Back hub mounts to standard 4" recessed outlet boxes. Dark bronze finish. Designed for use in wet locations. Lamp incl.

Catalog Number

WGH70H	70 watt MH, 120V, glass refractor, bronze	9 lbs
WGH100H	100 watt MH, 120V, glass refractor, bronze	10 lbs
WPH70S	70 watt HPS, 120V, polycarbonate refractor,	
	bronze	9 lbs
WPH100S	100 watt HPS, 120V, polycarbonate refractor,	
	bronze	9 lbs



Mid-size Refractor Wallpack

Cast aluminum housing and door for rugged mounting and protection of internal components. Non-yellowing glass refractor with coverage of four times mounting height laterally and two mounting heights forward. Typical mounting height is 12-15'. 1/2" conduit hubs on sides for surface conduit and top hub allows field installation of photocontrol. Back hub allows wiring access to recessed wiring boxes. Dark bronze finish. For use in wet locations. Lamp included.

Catalog Number

WGH175H	175 watt MH, 120, 208, 240, 277V, bronze	19 lbs
WGH150S	150 watt HPS, 120, 208, 240, 277V, bronze	18 lbs



Large Refractor Wallpack

Cast aluminum housing and door with protective dark bronze powder paint for lasting appearance. Glass refractor spreads output for coverage four times laterally and two times forward of typical 18-25' mounting height. 1/2" conduit hubs on side allow surface conduit wiring. Top hub allows location for field installed photocontrol. Back hub provides wiring access to recessed wiring boxes. For use in wet locations. Lamp included.

Catalog Number

WGH250H	250 watt MH, 120, 208, 240, 277V, bronze	34 lbs
WGH400H	400 watt MH, 120, 208, 240, 277V, bronze	37 lbs
WGH250S	250 watt HPS, 120, 208, 240, 277V, bronze	36 lbs
WGH400S	400 watt HPS, 120, 208, 240, 277V, bronze	40 lbs



Full Cutoff Wallpacks

Two sizes for total shielding at various mounting heights. Cast aluminum construction with stippled glass lens for lamp diffusion. Full cutoff shielding for environmentally-friendly distribution. Lateral coverage is three times typical mounting height of 8-15". 1/2" hubs allow surface conduit wiring or access to wiring boxes. Top hub allows easy field installation of photocontrol. Dark bronze finish. For use in wet locations. Lamp included.

Catalog Number

Compact Se	ries	
WGC50H	50 watt MH, 120, 277V, bronze	10 lbs
WGC70H	70 watt MH, 120, 208, 240, 277V, bronze	11 lbs
WGC100H	100 watt MH, 120, 208, 240, 277V, bronze	12 lbs
WGC100S	100 watt HPS, 120, 208, 240, 277V, bronze	12 lbs
Mid-Size Se	ries	
WGC175H	175 watt MH, 120, 208, 240, 277V, bronze	19 lbs
WGC150S	150 watt HPS, 120, 208, 240, 277V, bronze	18 lbs

CEILING/SURFACE



Ceiling/Surface Squares

Two series of surface mount units with wattage range from 70-175 watt. Rugged cast aluminum housing with vandal-resistant polycarbonate refractor. Typical mounting height is 8-15' with spacing of 10-20'. 1/2" conduit hubs on two sides allow surface conduit wiring. Top hub allows access to recessed junction boxes. Dark bronze protective finish. Designed for use in wet locations. Lamp included.

Cotol	~~	Nium	ha
Cata	υy	Nulli	nei

Compact 9'	' Square	
C9-70H	70 watt MH, 120, 208, 240, 277V, bronze	4.5 lbs
C9-70S	70 watt HPS, 120, 208, 240, 277V, bronze	4.5 lbs
Compact 12	?" Square	
C12-100H	100 watt MH, 120, 208, 240, 277V, bronze	6 lbs
C12-175H	175 watt MH, 120, 208, 240, 277V, bronze	6.75 lbs
C12-150S	150 watt HPS 120 208 240 277V hronze	7 lhe

DUSK-TO-DAWN



Dusk-To-Dawn

Three 175 watt mercury dusk-to-dawns provide a variety of security lighting solutions. Cast aluminum heads protect electrical components. Twistlock photocontrols save energy with automatic on/off; adjusts with the seasons. Long life "white" light lamp provides uniform lighting. All units are 120 volt. DD175C is UL listed for wet locations.

DD175C	Wall mount, screw-on 9" optic, acrylic refractor	
	120V photocontrol, lamp, prewired, UL listed	12 lbs
DDR175C	24" aluminum arm mount, latch-on 12" optic,	
	acrylic refractor, 120V photocontrol,	
	terminal block wiring, lamp	15 lbs
DDC175C	24" aluminum arm mount, latch-on full cutoff	
	reflector, 120V photocontrol, terminal block wir	ing,
	lamp	15 lbs

NDUSTRIAL



Industrial Hibay/Lobay

Ruggedly built industrials with cast aluminum ballast housing for heat dissipation and long ballast life. Cast aluminum safety hook included. 3/4" top hub on easy wire box. 400 watt metal halide lamp included. 16" diameter optics.

Typical mounting height: Hibay 18'-25'/Lobay 14'-20'.

Catalog Number

HB400H	Hibay, 400 watt MH, 120, 208, 240, 277V, white	
	24 lbs	
LB400H	B400H Lobay, 400 watt MH, 120, 208, 240, 277V, white	
	24 lbs	

WE'RE READY TO HELP YOU MAXIMIZE SALES!

4' MERCHANDISING DISPLAY







A DISPLAY HEADER TO FIT AN EXISTING GONDOLA



Due to our continued efforts to improve our products, product specifications are subject to change without notice.



Alera Lighting • Architectural Area Lighting • Columbia Lighting • Devine Lighting • Dual-Lite • Hubbell Outdoor Lighting

Hubbell Industrial Lighting • Kim Lighting • Moldcast • Prescolite • Prescolite Life Safety • Progress Lighting

Security Lighting Systems • Spaulding Lighting • Sterner Lighting Systems • Sportsliter Solutions • Whiteway

Hubbell Lighting, Inc.

UNITED STATES • Hubbell Lighting, Inc. • 101 Corporate Drive • Spartanburg, SC 29303 • PHONE: 864-599-6000 CANADA • Hubbell Canada • 870 Brock Road • Pickering, Ontario L1W 1Z8 • www.hubbell-canada.com

MEXICO • Hubbell De Mexico, S.A. DE.CV • Av. Coyoacan No. 1051 • Col.Del Valle • 03100 Mexico, D.F. • www.hubbell.com.mx