


TYPE GRC

Features

- Manufactured from seamless bronze tubing
- Supplied with silicon bronze screw
- Suitable for grounding and bonding in applications such as swimming pools and spas
- Copper conductor only

Benefits

- Provides maximum strength and superior conductivity
- Ground rod clamp is suitable for direct burial in earth or concrete



Catalog Number	Ground Rod Size	Ground Wire Range	Rebar Size	Rebar Wire Range	Dimensions	
					L	W
GRC-38	3/8	4-10	#3	4-10	5/8	5/8
GRC-58+	5/8	2-8	-	-	15/16	7/8
GRC-68	3/4, 5/8	2-8 for 3/4 rod, 1/0-8 for 5/8 rod	#5	1/0-8	1	1
GRC-75*	3/4	3/0-8	-	-	3/4	1-5/32

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Plain copper finish.

+ RUS Listed.

* Not UL Listed.

Tested to UL 467, UL File E34440


TYPE GRC

Features

- Manufactured from seamless bronze tubing
- Supplied with silicon bronze screw
- Suitable for grounding and bonding in applications such as swimming pools and spas
- Copper conductor only

Benefits

- Provides maximum strength and superior conductivity
- Ground rod clamp is suitable for direct burial in earth or concrete



Catalog Number	Ground Rod Size	Ground Wire Range	Rebar Size	Rebar Wire Range	Dimensions	
					L	W
GRC-38	3/8	4-10	#3	4-10	5/8	5/8
GRC-58+	5/8	2-8	-	-	15/16	7/8
GRC-68	3/4, 5/8	2-8 for 3/4 rod, 1/0-8 for 5/8 rod	#5	1/0-8	1	1
GRC-75*	3/4	3/0-8	-	-	3/4	1-5/32

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Plain copper finish.
+ RUS Listed.
* Not UL Listed
Tested to UL 467, UL File E34440


TYPE GRC

Features

- Manufactured from seamless bronze tubing
- Supplied with silicon bronze screw
- Suitable for grounding and bonding in applications such as swimming pools and spas
- Copper conductor only

Benefits

- Provides maximum strength and superior conductivity
- Ground rod clamp is suitable for direct burial in earth or concrete



Catalog Number	Ground Rod Size	Ground Wire Range	Rebar Size	Rebar Wire Range	Dimensions	
					L	W
GRC-38	3/8	4-10	#3	4-10	5/8	5/8
GRC-58+	5/8	2-8	-	-	15/16	7/8
GRC-68	3/4, 5/8	2-8 for 3/4 rod, 1/0-8 for 5/8 rod	#5	1/0-8	1	1
GRC-75*	3/4	3/0-8	-	-	3/4	1-5/32

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Plain copper finish.

+ RUS Listed.

* Not UL Listed.

Tested to UL 467, UL File E34440