





UPC Code: 07847732606 Country Of Origin: Mexico

NEMA: Non-NEMA



# **CS8265C**

#### **Brand Features**

Leviton's Black &White 50 Amp, Non-NEMA line of industrial grade locking blade devices feature rugged construction that resists impact, sunlight, chemicals and rough use. All contacts and blades are solid one-piece construction for superior conductivity. Corrosion resistant versions feature nickel plated contacts and blades, plus stainless steel shrouds and screws. The ergonomic, fluted-body design with radial gripping edge is ideal for gripping and pulling. The unique cord clamp accepts a wide range of cord sizes, providing a secure grip without damaging the cord. And, they are backed by a limited lifetime warranty.

#### **Item Description**

50Amp, 250V AC, Non-NEMA, 2P, 3W, Black & White Locking Plug, Industrial Grade, Grounding, California-Style(CS) - BLACK-WHITE

#### **Technical Information**

**Electrical Specifications Grounding:** Grounding Amperage: 50 A Voltage: 250 VAC

Pole: 2 Wire: 3

**Dielectric Voltage Withstand:** 2000V minimum per UL 498

Maximum Working Voltage: 250V as

Current Interrupting: Certified for current interrupting at full rated current

Temperature Rise: Max 30°C temp rise at full-rated current after 150 cycles of OL at 150% rated DC current

**Environmental Specifications** 

Flammability: Rated HB or better UL94

Operating Temperature: -40°C to 75°C

Environment: Dry

Material Specifications Face Module: Nylon Wiring Chamber: Nylon **Assembly Screws: Brass** Housing Material: Nylon Dust Shield: Santoprene TPE

Terminal Block: 0.062inch thick Copper Terminal Set Screw: SS 302/304

**Ground Shunt: Bronze Ground Post: Brass** 

Plug Blade: 0.1000inch thick Brass Plug Blade Shroud: SS 302/304 Standard Cable Clamp: Nylon Cable Clamp Screw: Philips Head, SS

Color: Black-White

Mechanical Specifications

Terminal ID: X, W, Y, Z and Green for

ground

Terminal Accom.: #10 min to #4max

AWG Solid or Stranded Wire

Product ID: Ratings and Catalogue No. molded into face and stamped into

shroud

Cord Range: .680 - 1.125

**Product Features NEMA:** Non-NEMA Color: Black-White


UL 498: File E13399

Device Type: Locking Plug Brand: Black and White Standards and Certifications

CSA C22.2 No. 42: File 152105

**NOM: 057** RoHS: Compliant

Warranty: Lifetime Limited



## SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

## Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747
Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

# Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

## Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

## Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

