



Color: White

UPC Code: 07847771804
Country Of Origin: China

HB011-PDX

Brand Features

Fixture Mount Passive Infrared High/Low Bay Occupancy Sensor, Time Delay: 30s-30m, (2) interchangeable, adjustable 360° lenses, the high bay PIR lens provides 1.5:1 spacing to mounting height coverage for 21-40 ft, the low bay lens provides 2:1 spacing to mounting height coverage for 13-20 ft, 120-230-277 or 347VAC, UL Listed, meets energy code requirements for ASHRAE 90.1 and Title 24.

Item Description

High Bay Fixture Mount Occupancy Sensor with Daylight Harvesting—PIR technology, Single relay with one (1-10VDC sinking current) control line for use to connect directly to low voltage control ballast. Examples i.e. Advance Mark VII or Leviton Sector 7, ballast. 21" Leads, 120-277V, 50/60Hz. Color: White

Features and Benefits

- 1-100% continuous dimming control
- Specifically designed for LED fixture control
- Suitable for use in standard cold storage applications
- Visual RGB LED indicators for device status and troubleshooting
- Alternating relay software for increased lamp life
- UL listed for electronic ballast loads 120/277V

SPECIFICATION SUBMITTAL

١	JOB NAME:	CATALOG NUMBERS:
I		
I	JOB NUMBER:	

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

