

STARSTRAND®

Re-Connectable

Basic Star



Features

- 3500° K color temperature
 - 96 Lumens/Foot
 - 1.4 Watts/Foot
 - 70-75 CRI
 - 120° beam spread
 - Runs up to 33 feet on a single driver
 - Field cuttable every 2"
 - No heat and no UV radiation
 - Soldered connectors supplied on each end
 - Additional and optional accessories allow for connection after being cut.
- Dimmable with optional low-voltage magnetic wall dimmer
 - ETL approved for damp locations

Applications

- Cove and toe kick accent lighting
- Cabinet lighting
- Architectural features
- Point of purchase displays
- Backlighting of signs and displays
- Wine cellars
- Closets

Item	Length	Diodes	Watts	Lumens	Current
53201	196"	300	24	1584	2A

Channel

Channel Star 24 3500° K



Features

- 3500° K color temperature
 - 222 Lumens/Foot
 - 4.32 Watts/Foot
 - 70-75 CRI
 - 120° beam spread
 - Runs up to 32 feet on a single driver
 - Rigid aluminum channel, available in Anodized Bronze or Brushed Aluminum finishes conceals light source and provides excellent heat dissipation
 - Connect end to end with/without cords
- Dimmable with optional remote control or low-voltage magnetic wall dimmer
 - ETL approved for damp locations
 - Includes easy to install mounting clips, both downward and 45° angle

Applications

- Under cabinets and bars
- Office desk task lighting
- Closet lighting
- Window displays

Item	Length	Diodes	Watts	Lumens	Current
53700 AL, BRZ	6"	10	2.16	111	120mA
53701 AL, BRZ	12"	18	4.32	222	180mA
53702 AL, BRZ	24"	36	8.64	444	360mA
53703 AL, BRZ	36"	54	12.96	666	540mA
53704 AL, BRZ	48"	72	17.28	888	720mA

CounterMax® Solution

MX-LMC Mini LED Channel



- 53800-BRZ 40" Starter Kit
- 53802-BRZ 66" Starter Kit
- 53804-BRZ 30" Expansion Kit

- Designed to illuminate drawers and cabinets
- Only 1/4" wide
- Easy to install and conceal
- Warm white 3000° K color temperature
- CRI 85, 120° beam spread
- 12V low voltage lighting system
- Aluminum channel
- Installs both flat and 45° angle using included mounting clips
- Optical lens focuses light where needed
- Optional touch dimmer and motion sensor available
- Available in a starter kit and an expansion kit
- Starter kit includes 12V driver

Length	Diodes	Watts	Lumens
5"	12	0.96	65
10"	24	1.92	130
16.5"	42	3.36	227

Channel Star 24 5000° K



Features

- 5000° K color temperature
 - 244 Lumens/Foot
 - 4.32 Watts/Foot
 - 70-75 CRI
 - 120° beam spread
 - Runs up to 32 feet on a single driver
 - Rigid aluminum channel, available in Anodized Bronze or Brushed Aluminum finishes conceals light source and provides excellent heat dissipation
 - Connect end to end with/without cords
- Dimmable with optional remote control or low-voltage magnetic wall dimmer
 - ETL approved for damp locations
 - Includes easy to install mounting clips, both downward and 45° angle

Applications

- Under cabinets and bars
- Office desk task lighting
- Closet lighting
- Jewelry cabinets

Item	Length	Diodes	Watts	Lumens	Current
53710 AL, BRZ	6"	10	2.16	122	120mA
53711 AL, BRZ	12"	18	4.32	244	180mA
53712 AL, BRZ	24"	36	8.64	488	360mA
53713 AL, BRZ	36"	54	12.96	732	540mA
53714 AL, BRZ	48"	72	17.28	976	720mA



For over 40 years, Maxim Lighting has defined lifestyle lighting, offering a variety of high-quality, decorative fixtures for the home; including chandeliers, sconces, pendants, ceiling mounts, bath vanities and outdoor lighting. Design inspiration from around the world characterizes our collections from the traditional to the unusual. Our exclusive products complement your distinct sense of style and add a touch of flair to every setting. Whether it's an elegant chandelier to complete your dining room or a set of beautiful pendants to enhance your kitchen, you're certain to discover just the right product at Maxim Lighting.



Maxim Lighting International, Inc.
253 North Vineland Avenue
City of Industry, California 91746 USA

General Info: 626.956.4200
Customer Service: 800.486.2947
Fax: 626.956.4228



facebook.com/maximlighting



Maxim Lighting's Web Site is your resource for detailed product information, including specification data, spec sheets, and high resolution images with detailed zoom features. Visit www.maximlighting.com today!

StarStrand and Maxim Lighting are registered trademarks of Maxim Lighting International, Inc. Maxim Lighting and all designs, logos, products and images © 2012 Maxim Lighting International, Inc. All Rights Reserved. Printed in USA. LMXBRO1207 1202.

Your Maxim Lighting Authorized Dealer:



StarStrand® LED Tape & Channel



STARSTRAND®

maximlighting.com/starstrand

White

Ultima Star 24



- Features**
- 3500° K color temperature
 - 241 Lumens/Foot
 - 4.32 Watts/Foot
 - 70-75 CRI
 - 120° beam spread
 - Runs up to 100 feet on a single driver
 - Field cuttable every 4"
 - Plastic covered to reduce static failure
 - Multiple lengths with soldered connectors for trouble free installation
 - Dimmable with optional remote control or low-voltage magnetic wall dimmer
- UL approved for damp locations
 - Highly flexible material that is backed with 3M adhesive for easy installation
- Applications**
- Office task lighting
 - Under cabinet lighting
 - Closets
 - Work areas
 - Display counters Steps and railings

Item	Length	Diodes	Watts	Lumens	Current
53450	4"	6	1.44	80	60mA
53451	12"	18	4.32	241	180mA
53455	20"	30	7.2	401	300mA
53452	60"	90	21.6	1205	900mA
53453	120"	180	43.2	2410	1.8A
53454	240"	360	86.4	4820	3.6A

Warm & Adjustable

Solar Star 24



- Features**
- 2700° K color temperature
 - 239 Lumens/Foot
 - 3.5 Watts/Foot
 - 70-75 CRI
 - 120° beam spread
 - Runs up to 148 feet on a single driver
 - Field cuttable every 4"
 - Plastic covered to reduce static failure
 - Multiple lengths with soldered connectors for trouble free installation
 - Dimmable with optional remote control or low-voltage magnetic wall dimmer
- UL approved for damp locations
 - Highly flexible material that is backed with 3M adhesive for easy installation
- Applications**
- Office task lighting
 - Under cabinet lighting
 - Closets
 - Work areas
 - Display counters
 - Steps and railings

Item	Length	Diodes	Watts	Lumens	Current
53470	4"	6	1.17	80	60mA
53471	12"	18	3.5	239	180mA
53472	60"	90	17.5	1195	900mA
53473	120"	180	35	2390	1.8A
53474	240"	360	70	4790	3.6A

Color Changing

Rainbow Star 24



- Features**
- Thousands of colors on one tape
 - 4.32 Watts/Foot
 - 120° beam spread
 - Runs up to 30 feet on a single driver
 - Field cuttable every 4"
 - Plastic covered to reduce static failure
 - Multiple lengths with soldered connectors for trouble free installation
 - Controlled with included RF remote control or optional DMX interface or optional Color Dial
 - ETL approved for damp locations
- Highly flexible material that is backed with 3M adhesive for easy installation
- Applications**
- Cove and toe kick accent lighting
 - Restaurants, bars and lounges
 - Store front displays
 - Back lighting of glass and acrylic panels
 - Game and theater rooms
 - Discos and clubs

Item	Length	Diodes	Watts	Lumens	Current
53530	4"	6	1.44	-	60mA
53531	12"	18	4.32	-	180mA
53533	60"	90	21.6	-	900mA
53534	120"	180	43.2	-	1.8A
53535	240"	360	86.4	-	3.6A

Outdoor

Aqua Star 24



- Features**
- 3500° K color temperature
 - 128 Lumens/Foot
 - 2.88 Watts/Foot
 - 70-75 CRI
 - 120° beam spread
 - Runs up to 50 feet on a single driver
 - Field cuttable every 4"
 - Waterproof IP68 LED tape
 - Chemical and UV resistant plastic cover
 - Installs into aluminum channel or plastic mounting clips
- Multiple lengths with watertight IP68 connectors
 - Dimmable with optional low-voltage magnetic wall dimmer
- Applications**
- Swimming pools and fountains
 - Outdoor decks, steps and stairs
 - Landscape lighting
 - Outdoor building accent lighting
 - Driveway and sidewalk illumination

Item	Length	Diodes	Watts	Lumens	Current
53441	24"	36	5.76	256	240mA
53442	60"	90	14.4	640	600mA
53443	120"	180	28.8	1280	1.2A
53445	300"	450	72	3200	3A

Elite Star 24



- Features**
- 3500° K color temperature
 - 153 Lumens/Foot
 - 2.88 Watts/Foot
 - 70-75 CRI
 - 120° beam spread
 - Runs up to 150 feet on a single driver
 - Field cuttable every 4"
 - Plastic covered to reduce static failure
 - Multiple lengths with soldered connectors for trouble free installation
 - Dimmable with optional remote control or low-voltage magnetic wall dimmer
- UL approved for damp locations
 - Highly flexible material that is backed with 3M adhesive for easy installation
- Applications**
- Cove and toe kick accent lighting
 - Outdoor covered porch and patio
 - Under cabinet lighting
 - Step lighting
 - Restaurants and lounges
 - Boats and RVs

Item	Length	Diodes	Watts	Lumens	Current
53430	4"	6	0.96	51	40mA
53431	12"	18	2.88	153	120mA
53432	60"	90	14.4	765	600mA
53433	120"	180	28.8	1530	1.2A
53434	240"	360	57.6	3060	2.4A

Color Flex Star 24



- Features**
- 2900° K to 500° K adjustable color temperature
 - 45-50 Lumens/Foot
 - 2.88 Watts/Foot
 - 70-75 CRI
 - 120° beam spread
 - Runs up to 20 feet on a single driver
 - Field cuttable every 4"
 - Plastic covered to reduce static failure
 - Multiple lengths with soldered connectors for trouble free installation
 - Controlled with included wall dial or RF remote control
- ETL approved for damp locations
 - Highly flexible material that is backed with 3M adhesive for easy installation
- Applications**
- Cove and toe kick accent lighting
 - Outdoor covered porch and patio
 - Under cabinet lighting
 - Display cases
 - Restaurants and lounges
 - Bathroom lighting

Item	Length	Diodes	Watts	Lumens	Current
53550	4"	6	0.96	15-16.5	40mA
53551	12"	18	2.88	45-50	120mA
53552	60"	90	14.4	225-250	600mA
53553	120"	180	28.8	450-500	1.2A
53554	240"	360	57.6	900-1000	2.4A

Rainbow Channel Star 24



- Features**
- Thousands of colors
 - 4.32 Watts/Foot
 - 120° beam spread
 - Runs up to 30 feet on a single driver
 - Rigid aluminum channel conceals light source and provides excellent heat dissipation
 - Connect end to end with or without cords
 - Controlled with included RF remote control or optional DMX interface or optional Color Dial
 - ETL approved for damp locations
- Includes easy to install mounting clips, both downward and 45° angle
- Applications**
- Under cabinets and bars
 - Alcove lighting
 - Retail display cabinets and counters
 - Window displays
 - Sign illumination

Item	Length	Diodes	Watts	Lumens	Current
53720AL	6"	10	2.88	-	120mA
53721AL	12"	18	4.32	-	180mA
53722AL	24"	36	8.64	-	360mA
53723AL	36"	54	12.96	-	540mA
53724AL	48"	72	17.28	-	720mA

Rainbow Aqua Star 24



- Features**
- Nine color modes and movement
 - 4.32 Watts/Foot
 - 120° beam spread
 - Runs up to 30 feet on a single driver
 - Field cuttable every 4"
 - Waterproof IP68 LED tape
 - Chemical and UV resistant plastic cover
 - Installs into aluminum channel or plastic mounting clips
 - Multiple lengths with watertight IP68 connectors
- Controlled with optional RF controller
- Applications**
- Swimming pools and fountains
 - Outdoor living areas
 - Landscape lighting
 - Outdoor architectural features
 - Signs
 - Outdoor walkways

Item	Length	Diodes	Watts	Lumens	Current
53541	24"	36	8.64	-	360mA
53542	60"	90	21.6	-	900mA
53543	120"	180	43.2	-	1.8A
53545	300"	450	108	-	4.5A