



Residential/Construction, Power Outlets & Temporary Power

Product #: M038CB1033

Short Description: 100A SURFACE MTRD 20/20GFCl/20GFCl

SPEC			NIC
SPEC	ICAI	IU	INC

OI LOII IOAT IOIG	
Category	Pow er Outlets & Temporary Pow er
Mounting	Surface
Heads	1
Metering	Ring-Type
Receptacles	6-20R, (2) 5-20R2GFCI
Feed	Overhead/Underground
AIC	10,000
Amps	100.0
Cabinet Size	14 X 26
Circuit Protection	Yes
Hub Provision	Yes
Installed Breaker	GFI220, (2) CB120
Load Center	LC55N1
Loop Feed	No
Phase	1
Suitable for Service Equipment	Yes
Standard Package	1
Stock Class Code	Stock
Certification	UL
Unit Weight	33.0
UPC	078456756486
Volts	120/240

Photo Not Available

Photo Not Available

Midw est Electric's Temporary Pow er and Pow er Outlets are a means of providing pow er required by various construction trades, residential sites, and mobile electrical applications. Temporary Pow er and Pow er Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against w eather, vandalism, and normal field use.

Copyright Midw est Electric Products, Inc. 2006