

## MB4A10C2

**Article Number:** 151-28421

**Adhesive Bases, .18" Max tie width, 1.12" Length/Width, .18" Hole Dia., PA66, White, 100/pkg**



### Base Data

**Local Order Number** MB4A10C2

**Type** MB4A

**Color** White (WH)

- Features and Benefits**
- For use with 18 and 30 pound cable ties to provide stability when securing bundles.
  - Secures with rubber based adhesive backing and/or two or four screws.
  - 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

**Product Description** HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

**Fixation Method (FF)** Screw Mounting and Adhesive

**Short Description** Adhesive Bases, .18" Max tie width, 1.12" Length/Width, .18" Hole Dia., PA66, White, 100/pkg

### Product Dimensions

**Length L (imperial)** 1.12 "

**Length L (metric)** 28.5 mm

**Width W (imperial)** 1.12 "

**Width W (metric)** 28.5 mm

**Cable Tie Width Max (imperial)** 0.18 "

**Cable Tie Width max. (metric)** 4.6 mm

**Height H (imperial)** 0.22 "

**Height H (metric)** 5.6 mm

**Mounting Hole Diameter D (imperial)** 0.18 "

**Mounting Hole Diameter D (metric)** 4.6 mm

**Mounting Hole Centers (imperial)** 0.8 "

**Mounting Hole Centers (metric)** 20.2 mm

### Logistics and Packaging

**Quantity per** bag

**Package Quantity** 100

**Carton Quantity** 4000

### Material and Specifications

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Adhesive** Synthetic rubber with base of polyethylene foam

**CSA Certified** No

**Flammability** UL94 V2 (excluding adhesive)

**Operating Temperature** -40 °F to +185 °F (-40 °C to +85 °C)

**ROHS Conformity** Yes

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes