


Slim-Line Wallpack/Flood LED Series



71390/71391 (20W & 30W)

71392/71393 (50W & 80W)
Shown with 71397 Trunion Mount (Sold Separately)



71396
1/2" Knuckle



71395/71397
Bracket/Trunion



71398
Slipfitter

Mounting & PhotoCell Applications

- ▶ Optional Mounting Accessories: 71320, 71323, 71324, 71325, 71328, 71329, 71395, 71396, 71397, 71398 - Sold Separately
- ▶ 71320 Junction Box Included with all fixtures **except** 71322, 71326, 71327 - (Junction Box Sold Separately for these 3 Cat#s)
- ▶ 71320 Junction Box is required In Photocell applications for 71322, 71326, 71327 Fixtures
- ▶ Cat# 39063 Photocell Extension required on 71322, 71326 & 71327 Fixtures for Photocell applications
- ▶ See Pg AA3 for Morris Pencil Style Photocell & Photocell Extension

- ▶ Cree CXA LEDs
- ▶ Integral Cooling Fin Releases the Heat Efficiently to Maintain the Life of LEDs & LED Driver
- ▶ Corrosion Resistant Die Cast Aluminum Housing
- ▶ Tempered Glass Lens
- ▶ Anodized Aluminum Optical Reflector
- ▶ Superior Architectural Bronze Powder Coat Finish
- ▶ Stainless Steel Hardware
- ▶ 3 Standard Knockouts to Screw in Optional Photocontrol

- ▶ Voltage: 120/208/240/277VAC
- ▶ Color Temperature: 5000K Cool White
- ▶ Light Pattern: 140° Beam Angle
- ▶ Operation Temperature: -40°F to 131°F
- ▶ 50,000+ Hour LED Life Expectancy
- ▶ IP65 (NEMA 4X) Dust & Water Tight
- ▶ 4 Threaded Apertures - (4) Sides
- ▶ cULus listed for Wet Locations
- ▶ DLC Listed - 5 Year Warranty


Cat. No.	Watts	Delivered Lumens	Replaces Metal Halide	CRI	Dimensions				Weight (Lbs.)	Case Qty
					L	H	W1	W2		
71390	20	1874	50W	75	6-1/2"	7-3/4"	1-1/2"	2-3/8"	4	6
71391	30	2687	70W	72	6-1/2"	7-3/4"	1-1/2"	2-3/8"	4	6
71392	50	4363	100W	83	9-1/2"	11-1/4"	2-3/8"	2-3/8"	10	2
71393	80	7371	175W	82	9-1/2"	11-1/4"	2-3/8"	2-3/8"	10	2

Accessories

Cat No.	Description	Applicable Fixture	Weight (Lbs)	Case Qty
71395	Bracket Mount	71390/71391 (20W & 30W)	.5	30
71396	1/2" Adjustable Knuckle Mount	71390/71391 (20W & 30W)	.5	30
71397	Trunion Mount	71392/71393 (50W & 80W)	1.1	10
71398	Slipfitter Mount	71392/71393 (50W & 80W)	2.9	5



71321/71322
(22W & 40W)



71320



71328



71326/71327
(86W & 153W)



71323



71329

Cat. No.	Watts	Delivered Lumens	Replaces Metal Halide	CRI	Dimensions				Weight (Lbs.)	Case Qty
					L	H	W1	W2		
71322	40	3687	100W	72	7-1/2"	8"	2-3/4"	2-7/16"	4	6
71326	86	6550	175W	83	14-1/4"	12-3/4"	4-7/8"	3-7/8"	12	1
71327	153	12,500	250W	82	14-1/4"	12-3/4"	4-7/8"	3-7/8"	12	1

Accessories

Cat No.	Description	Applicable Fixture	Weight (Lbs)	Case Qty
71323	1/2" Adjustable Knuckle Mount	71322 (40W)	2.5	12
71324	Slipfitter Mount	71322 (40W)	4.6	12
71325	Trunion Mount	71322 (40W)	3.3	12
71328	Trunion Mount	71326 & 71327 (86W & 153W)	4.6	12
71329	Slipfitter Mount	71326 & 71327 (86W & 153W)	6.4	12
71320	Optional Junction Box	Wall Mount Applications	2.0	12

LED
Lighting

CC8