


LIGHT ROPE




SCHEMATICS:



3/8" DIAMETER LENGTHS

- ▶ Bulk Packaging:
Every 3 foot increment between 3' and 99' (clear color only).
- ▶ Retail Packaging:
3', 6', 12', 18', 24', 30', 150'



1/2" DIAMETER LENGTHS

- ▶ Retail Packaging only:
3', 6', 12', 18', 24', 30', 150'

DESCRIPTION:

Long life Incandescent bulbs extruded in a flexible light strip that plugs into a standard 110 VAC wall outlet. Light bulbs are rated at 20,000 hour avg. bulb life and consume only 2.16 watts per foot. All Light Rope sections have molded on connectors and screw together to a maximum single run of 450 ft. Offered in J-Rack ready retail packaging (3/8" dia. and 1/2" dia.), and economic bulk packaging (3/8" dia. only). Dimmable with a standard 110 VAC rheostat. UL listed to 2388 Flexible Lighting Standard for all indoor and outdoor applications. Offered in six Light Rope colors. See Specifications below and instructions for all options and installation details.

APPLICATIONS

- ▶ Cove lighting
- ▶ Eave lighting
- ▶ Deck lighting
- ▶ Cabinet lighting
- ▶ Architectural outlines
- ▶ Visual merchandising
- ▶ Exhibit projects
- ▶ Stage lighting
- ▶ Theatrical projects

FEATURES

- ▶ UL listed and labeled to tough 2388 Flexible Lighting Products standard for indoor and outdoor applications.
- ▶ Ships completely assembled and ready to mount. All packaging includes Light Rope, fused power cord, and mounting clips.
- ▶ Sold in both J-Rack ready retail packages and polybag bulk packing (see instructions).
- ▶ Sold in both 1/2" diameter and 3/8" diameter.
- ▶ Interconnectable to 450 ft. per 110V plug.
- ▶ Crushproof to 150 PSI.
- ▶ 30,000 hour average bulb life.
- ▶ Available in six colors

ORDERING LOGIC:

RLR10-ZZ-YY = Retail Packaging 3/8" diameter
 RLR13-ZZ-YY = Retail Packaging 1/2" diameter
 BLR10-ZZ-32 = Bulk Packaging 3/8" diameter

ZZ = LIGHT ROPE LENGTH

Example: 3 = 3 foot
 99 = 99 foot

YY = LIGHT ROPE COLOR

30 = Red 33 = Orange
 31 = Blue 34 = Green
 32 = Clear 35 = Yellow

SPECIFICATIONS:

Voltage	110VAC
Bulb Specifications	3.5 volt, 50mA, .18 watts
Average Bulb Life	30,000 Hours
Bulb Spacing	1" on Center
Colors	Clear, Red, Blue, Orange, Green, Yellow
Diameter	1/2" (13mm) and 3/8" (10mm)
Lengths	Retail Packaging (Blister Packed - 1/2" diameter and 3/8" diameter, all color options): 3', 6', 12', 18', 24', 30', 150' Bulk Packaging (Polybag Packed - 3/8" Diameter Clear ONLY): 3', 6', 9', 12', 15', 18', 21', 24', 27', 30', 33', 36', 39', 42', 45', 48', 51', 54', 57', 60', 63', 66', 69', 72', 75', 78', 81', 84', 87', 90', 93', 96', 99'
Interconnectability	All lengths of equal diameter can connect together to a maximum of 450 ft. per 110V plug.
Power Cord	Every packaged length comes with a 6-foot fused SJT power cord per UL 2388 requirements. Required for outdoor applications. Includes one spare fuse in every power cord plug.
Mounting	Every packaged length comes with Mounting Clips for every 2' of product. Mounting Clips screw to surface, and Light Rope presses into clip (screws included). Do not mount or route cords or flexible lighting through walls, ceilings, floor, doors, windows or any part of a building structure.
Field Modification	Per UL 2388, there is no cutting, splicing, or field modification allowed. Once a section's life has expired, the length must be disconnected, disposed of, and replaced.
Maximum Run	Interconnectable to 450 ft. per 110V plug.
Energy Usage	2.16 watts per foot
Agency Approval	UL listed Indoor & Outdoor to tough UL 2388 standards.



PROJECT:	TYPE:
NOTES:	