

TOOLS

Torque Wrenches, Screwdriver & Accessories

TW SERIES



FEATURES

TORQUE WRENCHES

- Dual scale, calibrated dual direction.
- Positive lock with spring loaded pull down lock ring.
- Fast, accurate and easy to set.
- Easy-to-read laser marked scales.
- Most feature quick release buttons which provide good socket retention as well as easy socket removal.
- Accuracy: 3% CW, 4% CCW of indicated value, CW from 20% to 100% of full scale.
- Individually serialized with matching certificate of calibration traceable to N.I.S.T.

TORQUE SCREWDRIVERS

- Positive locking pull down adjustment knob.
- Trilobular comfort grip.
- Universal 1/4" hex bit holder with strong rare earth magnet.
- Cam-over torque limiting clutch and slip resistant finish.
- Easy-to-read window scale and light weight.
- Automatic lock in CCW direction for disassembly.
- Accuracy: 6% of indicated value, CW from 20% to 100% of full scale. Individually serialized with matching certificate of calibration traceable to N.I.S.T.
- Meets or exceeds ASME B107.14-2004

CAT. NO.	FIG. NO.	DESCRIPTION	STD. CTN. QTY.
TW20-150	1	Torque Wrench. Click Type. 20-150 In Lbs. 3/8" Drive Dual Scale.	1
TW100-750	2	Torque Wrench. Click Type. 100-750 In Lbs. 3/8" Drive Dual Scale.	1
TW5-40	3	Torque Screwdriver. Micro Adjustable. 5-40 In Lbs. 1/4" Drive Single Scale.	1
TWHB 3818	4	Hex Bit 3/8" Socket. 1/8" Hex.	1
TWHB 38316	5	Hex Bit 3/8" Socket. 3/16" Hex.	1
TWHB 3814	6	Hex Bit 3/8" Socket. 1/4" Hex.	1
TWHB 38516	7	Hex Bit 3/8" Socket. 5/16" Hex.	1
TWHB 3838	8	Hex Bit 3/8" Socket. 3/8" Hex.	1
TWHB 1212	9	Hex Bit 1/2" Socket. 1/2" Hex.	1
TWDA 3812	10	Drive Adaptor. 3/8" Female To 1/2" Male (Needed For Sa16a, Sa18a And Sa20a)	1
TWBS 14	11	13 Piece 1/4" Drive Insert Bit Set.	1
TWSB	12	Holder For 1/4" Hex Screwdriver Bit. 3/8" Drive.	1

