

# Compounds

## Type DUX

### Duct Sealing Compound

#### Use:

An ideal waterstop and moisture barrier for sealing between electrical cables and conduit ducts. A standard for weather sealing service entries.

#### Features:

- A soft, fibrous, slightly tacky, non-hardening sealing compound easily applied by hand at all working temperatures.
- Gray color, clean and non-staining
- Can be painted
- Excellent cohesive and adhesive properties

#### Third Party Certification:

 UL Listed: R-15320

#### Ordering Note:

When ordering DUX, specify number of units only, not lbs. For example: To order 50 lbs., specify 10 DUX-5 units.

Catalog Number	Pound Package
DUX-1	1
DUX-5	5



Type DUX

## Type WQ

### Wire-Quick Wire Pulling Compound


#### Use:

"Wire Quick" lubricates wire and cable to substantially reduce the pulling tension required.

#### Features:

- It has excellent adhesion and will not crumble.
- Completely safe for use on all insulations... rubber, lead and plastics. and "WIRE QUICK" can be used with all types of conduit. It's non-corrosive and non-combustible.
- "WIRE QUICK", after a period of time in a conduit, will dry and leave a film. This acts as a lubricant in the event the wire or cable must be removed.
- Skin and clothing will not be harmed by Wire-Quick compound. It also washes easily from hands.


#### Third Party Certification:

 UL Listed: E-76536

#### Ordering Note:

When ordering WIRE QUICK specify by number of units only, not gallons. For example: To order 50 gallons, specify 10 WQ-05 units.

Catalog Number	Unit
WQ-00	1 Qt. Can
WQ-01	1 Gal. Pail
WQ-05	5 Gal. Pail
WQ-55	55 Gal. Drum



Type WQ