
6X4 BASIC COMBO MODULE

364400-04 | [On-Q](#)



FEATURES & BENEFITS

Supports telecom distribution to outlets via 110-style punchdown connections and video distribution. Does not include telecom surge protection, telecom expansion or security system interface.

5 1/8"H x 6 1/2"W

- Compact design provides maximum space for system modules
- Supports four-line telecom service distribution and video service distribution to room outlets

SPECIFICATIONS

GENERAL INFO

Color: Black
Finish: Powder Coat
Type: Telecom/Video Module

ASSEMBLY/INSTALLATION INFORMATION

Mounting Hardware Included: Yes

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

UN SPSC: 43222819

CONSTRUCTION INFORMATION

Installation Location: Enclosure

DIMENSIONS

Height (Metric): 13 cm
Height (US): 5.125"
Length (Metric): 3.28"
Length (US): 8.3 cm
Width (Metric): 16.5 cm
Width (US): 6.5 in

TECHNICAL INFORMATION

Bracket Required: Mounting plate 100356-01 included
Frequency: 5-1000 MHz
Humidity: 90% Relative Humidity (Non-Condensing)
Material: 18 Gauge CRS
Mounting: Mount directly in any On-Q style enclosure
Operating Temperature (Celsius): 0°C to 50°C
Output Impedance: 75 ohms
Product Fits Into: On-Q Style Enclosure
Shape: Rectangular
Receptacle Type: 6x 110 Punchdown Telecom, 4x RG6 "F"
Number Of Receptacles: 10