


Polywater® Lubricant Pump Model LP-D5



The Polywater® Lubricant LP-D5 Pump is a 1/2-inch drill-operated, self-priming, gear pump. Now includes two hands-free applicators (small for 1 1/2 to 3-inch and large for 3 to 6-inch conduits). All Polywater® lubricants can be pumped directly into the conduit or onto the cable during cable installations at rates exceeding 1.5 gallons per minute.

The LP-D5 pump sets directly onto a 5-gallon pail or 55-gallon drum and comes with a 10-foot discharge hose with lubricant applicator.

Use your 1/2-inch drill to pump pulling lubricant from a 5-gallon pail or a 55-gallon drum.

Now includes two hands-free applicators for 1/2 to 6-inch conduits.

Advantages

- **Practical Transfer of all Polywater® Lubricants** – Save time and effort in cable pulling. Eliminate hand scooping, messy pouring, and lengthy clean-ups.
- **Variable Pumping Capability** – Adjustable speed 1/2-inch drill allows pump to deliver lubricants at a rate of 1.5 gallons per minute or higher.
- **Consistent Lubricant Application** – Automates lubricant application with consistent lubrication throughout installation.
- **Convenient** – No hand pumping. Requires battery or 1/2-inch electric variable speed drill.
- **Easy Maintenance** – Minimum assembly required. Cleans up with water.
- **Corrosion Resistant** – Solid brass body and stainless steel shaft.

Polywater® Lubricant LP-D5 Pump

Operation

For use on 55-gallon drum and 5-gallon pail Open pail or drum. With drum, untie and open liner, then replace drum cover. Set LP-D5 pump in 5-gallon pail or into the 2-inch bung hole of a 55-gallon drum. Attach variable speed drill to LPD5. Insert free end of hose into conduit opening, pail or jug. Set drill to OPERATE IN FORWARD. Start drill to pump lubricant until it is visible at hose end. If installing cable, start pulling cable and start variable speed 1/2-inch drill to pump lubricant at desired flow rate.

Cleaning

Pump clean tap water through LP-D5 pump until water discharge is clear. Let pump sit for 15 minutes. Run pump again with clean tap water to remove any remaining lubricant. Repeat the process as necessary. Wipe off pump and applicator. Protect from dirt with bag or other cover.

General

Keep dirt and debris away from pump to avoid damage. Avoid running pump dry to prevent damage.

Ordering Information

Catalog #	Description
LP-D5	Drill Powered pump for 5-Gallon Pail or 55-Gallon Drum. Includes 2 applicators (1/2-inch drill not included)

Suggested Polywater® Lubricants for pumping application:

Polywater® LZ Cable Pulling Lubricant: www.polywater.com/polylz.asp

Polywater® J Cable Pulling Lubricant: www.polywater.com/polyj.html

Polywater® PJ Pourable Cable Lubricant: www.polywater.com/polypj.html

To view technical information on our website go to:

Support Page: www.polywater.com/pumplpd5.asp

Application Videos: www.polywater.com/videos.asp



phone: 1-800-328-9384
1-651-430-2270
fax: 1-651-430-3634

email: support@polywater.com

11222 60th Street North, Stillwater, MN 55082, U.S.A.

ADHESIVES | CLEANERS | **LUBRICANTS** | SEALANTS

WWW.POLYWATER.COM

Important Notice: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from product's use, regardless of the legal theory asserted.