

# DISTRICT LED

Ceiling cord mounted • Damp location listed

## Specifications:

### Description:

The one-light medium size LED cord hung pendant/outdoor hanging lantern from the District Collection features metal shade that offers an industrial-inspired design. The versatile vintage form can be used in indoor and outdoor applications.

### Construction:

- Antique Bronze (-20) (painted)
- Aluminum construction
- LED Module is replaceable (Part # 93054049)
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)
- CA Title 24 compliant
- Canopy covers a standard 4" hexagonal recessed outlet box
- Mounting strap for outlet box included
- 10 feet of wire supplied

### Performance:

Number of Modules	1
Input Power	9W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	623/69.2 (LM-79) per module
CCT	3000K
CRI	90
Life	60000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30
Max. Operating Temp	30
Warranty	5 year warranty
Labels	cCSAus Damp location listed ENERGY STAR® qualified

### Catalog number:

Base	Finish	Color Temp	CRI
P5535	20 - Antique Bronze	30K - 3000K	9 - 90 CRI

## P5535-2030K9

### Images:



### Dimensions:

Diameter: 8"  
 Height: 6-1/4"  
 Overall ht. w/cord: 130"



# DISTRICT LED

Ceiling cord mounted • Damp location listed



## P5535-2030K9

### Dimming Notes:

---

P5535 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

### Electronic Low Voltage ELV Reverse Phase Controls

---

Lutron	Diva Series	(Part Number DVELV-300P)
--------	-------------	--------------------------

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.