LFP38A

Premium PAR38 Flood with large, molded high temperature black silicone gasket that totally seals lamp. Die cast aluminum housing. EZ Locknut. Suitable for mounting within 4' of the ground. PAR38 or PAR20, 150 watt max. Lamp not supplied.

Lamp Info **Ballast Info** PAR20 N/A Type: Type: Watts: 150W 120V: N/A 208V: Shape/Size: N/A N/A Base: N/A 240V: N/A ANSI: N/A 277V: N/A Hours: 2,500 Input Watts: 0W 550 Lamp Lumens: Efficiency: N/A Efficacy: N/A

Technical Specifications

UL Listing:

Suitable for wet locations.

Sockets:

Porcelain with all copper current carrying components and spring loaded center contact.

Swivels:

Fully adjustable with sure-grip locknuts. 1/2" NPS threaded arm with locking swivel fits all standard mounting covers.

Housings:

Precision die cast aluminum. Tuffy flood is molded plastic.

Lamp:

PAR38 or PAR20, 150 watt max. lamp not supplied.


Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

Color: Bronze







RAB

Copyright ©2013 RAB Lighting, Inc. All Rights Reserved

Tech Help Line: 888 RAB-1000

Email: sales@rabweb.com

On the web at: www.rabweb.com

Note: Specifications are subject to change without notice