## Rittal - The System.

Faster – better – everywhere.

## Hygienic DesignCompact enclosureHD – HD 1316.600

Date: May 29, 2018



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

## Hygienic Design Compact enclosure HD - HD 1316.600

created: 29.05.2018 build on www.rittal.com/us-en



<b>Prod</b>	uct	daen	rin	tion
riou	uci	uesu	,ı ıp	เเบา

Version: Roof slope 30° towards the front

Material: Housing and door: Stainless steel 1.4301 (AISI 304)

Mounting plate: Carbon steel

HD lock inserts: Stainless steel 1.4404 (AISI 316L)

Seal: Silicone, compliant with FDA Guideline 21 CFR 177.2600

Surface finish: Housing and door: Brushed, grain 400, peak-to-valley height < 0.8 μm

> Mounting plate: Zinc-plated Seal: Blue, dyed (RAL 5010)

**Protection category** 

IP to IEC 60 529:

**Protection category** IP to DIN 40 050-9:

IP 69K

IP 66

**Protection category** 

NEMA:

NEMA 13 **NEMA 4X** 

Supply includes: Housing of all-round solid construction

Door with fitted seal

Door catch on right, may be swapped to the left

Mounting plate

Base material: Stainless steel

## **Product features**

**Dimensions:** Height (front): 1050 mm (41 ")

Height (rear): 1221 mm (48 ")

Width: 810 mm (32 ")

© Rittal 2018 1 Depth: 300 mm (12 ")

Mounting plate:	Height: 955 mm (38 ") Width: 739 mm (29 ")
Number of cam locks:	1
Packaging unit:	1 pc(s).
Weight/packaging unit:	60.1 kg (132.5 lb.)
EAN:	4028177567641
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180102
Product description (long):	HD Compact enclosure, WHD: 810x1050(H1)x1221(H2)x300 mm, Stainless steel 1.4301, with mounting plate, with hinged door and silicone seal
Approvals	
Approvals:	UL + C-UL
Certificates:	DGUV EAC
Declarations:	Declaration of conformity

© Rittal 2018 2