Rittal - The System.

Faster – better – everywhere.

KS Plastic EnclosuresKS 1434.500

RITTAL

NCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

KS Plastic Enclosures - KS 1434.500

created: 24.05.2018 build on www.rittal.com/us-en



Varalanı	vide and visusing vineday.
Version:	without viewing window
Material:	Housing and door: Fiberglass-reinforced unsaturated polyester
	Door: All-round foamed-in PU seal
	Mounting plate: Carbon steel Viewing window: Glazed acrylic, 3.0 mm with all-round rubber cable clamp strip
	viewing window. Glazed acrylic, 3.0 mm with all-round rubber cable clamp strip
Surface finish:	Housing and door: Dyed plastic with no after-treatment
	Mounting plate: Zinc-plated
Color:	Similar to RAL 7035
Protection category	IP 66
IP to IEC 60 529:	
Protection category NEMA:	NEMA 4X
IK code:	IK08
Supply includes:	Housing with hinged door, of all-round solid construction, 3 mm double-bit lock
	Mounting plate
	Twin seal on the top and bottom edges of the door as integral rain protection strip Press-fitted C sections at the sides for infinitely variable mounting plate depth adjustment
Note:	Under the influence of long-term UV radiation (sunlight) in conjunction with wind and rain, the
	surface finish may become visually impaired. This does not affect the protection of the installed electrical components in any way. If the enclosures cannot be protected from UV radiation, we recommend that they should be painted with a PUR paint. Permissible ambient temperature - 30°C+75°C.
Base material:	Plastic

© Rittal 2018

Product features	
Dimensions:	Height: 400 mm (16 ") Width: 300 mm (12 ") Depth: 200 mm (7.9 ")
Material thickness::	Mounting plate: 2 mm (0.08 ")
Mounting plate:	Height: 350 mm (14 ") Width: 245 mm (9.6 ")
Number of doors:	1
Door catch on right, may be swapped to the left:	yes
Lock version:	Cam
No. of locks:	2
Lock Insert:	3 mm double-bit
Packaging unit:	1 pc(s).
Weight/packaging unit:	5.9 kg
EAN:	4028177526662
Customs tariff number:	94037000
ETIM 6.0:	EC000261
ETIM 5.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180102
Product description (long):	KS Plastic enclosure, WHD: 300x400x200 mm, Fibreglass-reinforced unsaturated polyester, with mounting plate, with door

Approvals

© Rittal 2018

Approvals:	Bureau Veritas Germanischer Lloyd Lloyds Register of Shipping Russian Maritime Register of Shipping TÜV
Certificates:	EAC IK-Code
Declarations:	Declaration of conformity

© Rittal 2018 3