

Rittal – The System.

Faster – better – everywhere.

► Wall-mounted cooling units TopTherm "Blue e" Total cooling output 0.50 – 0.75 kW – SK 3303.510

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wall-mounted cooling units TopTherm "Blue e" Total cooling output 0.50 – 0.75 kW – SK 3303.510

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Material: Carbon steel

Color: RAL 7035

**Protection category
IP to IEC 60 529:** External circuit, IP 34
Internal circuit, IP 54

Supply includes: Nano-coated condenser
Wired ready for connection (plug-in terminal strip)
Drilling template
Fasteners

Note: The technical specifications for the wall-mounted cooling unit 3361.540 are valid with an external transformer connected.

Product features

**Total cooling output
to DIN EN 14511:** L 35 L 35 at 60 Hz: 0.66 kW (2252 BTU)
L 35 L 50 at 60 Hz: 0.4 kW (1364 BTU)

**Air throughput
(unimpeded air flow):** External circuit: 345 m³/h (203.1 cfm)
Internal circuit: 280 m³/h (164.8 cfm)

**Rated operating
voltage:** 115 V, 1~, 60 Hz

Dimensions: Height: 550 mm (22 ")
Width: 280 mm (11 ")
Depth: 210 mm (8.3 ")

Temperature control:	e-Comfort Controller (factory setting +35°C)
Temperature range:	Operation (environment): +10°C...+55°C Setting range: +20°C...+55°C
Refrigerant/cooling medium:	Refrigerant: R134a Quantity: 170 g (6 oz) Global Warming Potential (GWP): 1430 CO ₂ equivalent (CO _{2e}): 0.24 t
Rated power P_{el}:	L 35 L 35 at 60 Hz: 0.5 kW L 35 L 50 at 60 Hz: 0.53 kW
Rated current (max.):	At 60 Hz: 5.7 A
Start-up current (max.):	At 60 Hz: 11.5 A
Miniature circuit-breaker/fuse:	10 A
Energy efficiency ratio (EER) 50 Hz L35 L35 to DIN EN 14511:	1.4
Packaging unit:	1 pc(s).
Weight/packaging unit:	17 kg (37.5 lb.)
EAN:	4028177322837
Customs tariff number:	84158200
ETIM 6.0:	EC000855
ETIM 5.0:	EC000855
eCl@ss 8.0/8.1:	27180704
eCl@ss 7.0/7.1:	27180704
eCl@ss 6.0/6.1:	27180704
eCl@ss 5.1/5.1.4:	27180704
Product description (long):	SK cooling unit Blue e, wall-mounted, 0.66 kW, 115 V, 1~, 60 Hz, Sheet steel, WHD: 280 x 550 x 210 mm

Approvals

Approvals: CSA
TÜV-Geprüfte Leistung
TÜV-Geprüfte Sicherheit
UL + C-UL - FTTA
UR + C-UR

Certificates: EAC

Declarations: Declaration of conformity
Declaration of conformity - F-gas regulation
