

Rittal – The System.

Faster – better – everywhere.

► Wall-mounted cooling units TopTherm "Blue e" Total cooling output 1.00 - 1.50 kW – SK 3305.510

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wall-mounted cooling units TopTherm "Blue e" Total cooling output 1.00 - 1.50 kW – SK 3305.510

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Material: Carbon steel

Color: RAL 7035

Protection category IP to IEC 60 529: External circuit, IP 34
Internal circuit, IP 54

Supply includes: Nano-coated condenser
Integral electric condensate evaporation
Wired ready for connection (plug-in terminal strip)
Drilling template
Fasteners

Note on Model No.:: Delivery times on request.

Product features

Total cooling output to DIN EN 14511: L 35 L 35 at 50 Hz: 1.6 kW (5459 BTU)
L 35 L 35 at 60 Hz: 1.76 kW (6005 BTU)
L 35 L 50 at 50 Hz: 1.25 kW (4265 BTU)
L 35 L 50 at 60 Hz: 1.37 kW (4674 BTU)

Air throughput (unimpeded air flow): External circuit: 805 m³/h (473.8 cfm)
Internal circuit: 585 m³/h (344.3 cfm)

Rated operating voltage: 115 V, 1~, 50 Hz/60 Hz

Dimensions: Height: 950 mm (37 ")

Width: 400 mm (16 ")
Depth: 260 mm (10 ")

Temperature control:	e-Comfort Controller (factory setting +35°C)
Temperature range:	Operation (environment): +10°C...+55°C Setting range: +20°C...+55°C
Refrigerant/cooling medium:	Refrigerant: R134a Quantity: 500 g (17.6 oz) Global Warming Potential (GWP): 1430 CO ₂ equivalent (CO _{2e}): 0.72 t
Rated power P_{el}:	L 35 L 35 at 50 Hz: 0.87 kW L 35 L 35 at 60 Hz: 0.98 kW L 35 L 50 at 50 Hz: 1.03 kW L 35 L 50 at 60 Hz: 1.15 kW
Rated current (max.):	At 50 Hz: 11.5 A At 60 Hz: 12.5 A
Start-up current (max.):	At 50 Hz: 26 A At 60 Hz: 28 A
Pre-fuse:	Transformer circuit-breaker: 14 A...20 A
Energy efficiency ratio (EER) 50 Hz L35 L35 to DIN EN 14511:	1.83
Packaging unit:	1 pc(s).
Weight/packaging unit:	46 kg (101.4 lb.)
EAN:	4028177322981
Customs tariff number:	84158200
ETIM 6.0:	EC000855
ETIM 5.0:	EC000855
eCl@ss 8.0/8.1:	27180704
eCl@ss 7.0/7.1:	27180704
eCl@ss 6.0/6.1:	27180704
eCl@ss 5.1/5.1.4:	27180704
Product description	SK cooling unit Blue e, wall-mounted, 1.6 kW, 115 V, 1~, 50/60 Hz, Sheet steel, WHD: 400 x

(long):

950 x 260 mm

Approvals

Approvals:

CSA
TÜV-Geprüfte Leistung
TÜV-Geprüfte Sicherheit
UL + C-UL - FTTA
UR + C-UR

Certificates:

EAC

Declarations:

Declaration of conformity
Declaration of conformity - F-gas regulation