

# Rittal – The System.

Faster – better – everywhere.

## LED compact system light – SZ 4140.830

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# LED compact system light – SZ 4140.830

created: 24.05.2018 build on [www.rittal.com/us-en](http://www.rittal.com/us-en)



## Product description

<b>Benefits:</b>	Max. EMC capacity. Protected with the safety extra-low voltage range Economical energy use. Low-maintenance with the use of LEDs. May be connected to a door-operated switch.
<b>Function principle:</b>	Integral through-wiring. Universal attachment options. Vertically hinged light cone.
<b>Material:</b>	Light body: Extruded aluminum Light cover: Polycarbonate (halogen-free) Light ends: PC-ABS
<b>Color:</b>	Similar to RAL 7035
<b>Protection category IP to IEC 60 529:</b>	IP 20
<b>Supply includes:</b>	LED compact system light Light (bulb) Light cover Assembly components
<b>Note:</b>	Only intended for use in enclosures and closed housings When using on customer-supplied power packs, it is important to obtain the requisite approvals depending on the application The maximum rated current when installing luminaires is 2 A

## Product features

**Dimensions:** Height: 32.8 mm (1.3 ")

Width: 430 mm (17 ")  
Depth: 20.64 mm (0.81 ")

<b>Rated operating voltage:</b>	24 V (DC) Voltage tolerance: ± 10 %
<b>Installation options:</b>	TS horizontal profile from roof frames: direct TS, SE vertical profile, direct SE profiles to the front and rear of roof frames: direct SE profiles to the side of roof frames: direct AE, CM, TP: with magnet mounting kit AE: with rail for interior installation
<b>Mounting dimensions:</b>	Mounting distance – clip/magnet: 375 mm (15 ") Mounting distance – screw attachment: 450 mm (18 ")
<b>Rated current:</b>	with DC (max.): 0.12 A Note: The maximum rated current when installing luminaires is 2 A
<b>Equipment (electrical):</b>	Light (bulb): LEDs, cool white Switch (type): Integral, on/off/door-operated switch mode
<b>Rated insulation voltage:</b>	Depending on the power supply
<b>Rated impulse withstand voltage, phase to earth:</b>	Depending on the power supply
<b>Rated impulse withstand voltage, phase to phase:</b>	Depending on the power supply
<b>Number of LEDs:</b>	30
<b>Protection category:</b>	III (SELV)
<b>Connection options:</b>	Power supply through connector Door-operated switch Through-wiring (configuration of row of luminaires)
<b>Light – installation type:</b>	Screw fastening Clip fastening Magnetic fastener (accessories)
<b>Light cover:</b>	yes
<b>Light cone adjustment:</b>	yes
<b>Packaging unit:</b>	1 pc(s).
<b>Weight/packaging unit:</b>	0.38 kg (0.8 lb.)
<b>EAN:</b>	4028177630147

<b>Customs tariff number:</b>	94054099
<b>ETIM 6.0:</b>	EC000321
<b>ETIM 5.0:</b>	EC000321
<b>eCl@ss 8.0/8.1:</b>	27189241
<b>eCl@ss 7.0/7.1:</b>	27189241
<b>eCl@ss 6.0/6.1:</b>	27189241
<b>eCl@ss 5.1/5.1.4:</b>	27189241
<b>Product description (long):</b>	SZ System light LED compact, WHD: 430x33x21 mm, 24 V DC, Integral on/off/door-operated switch mode
<b>Approvals</b>	
<b>Certificates:</b>	EAC
<b>Declarations:</b>	Declaration of conformity