

Rittal – The System.

Faster – better – everywhere.

Door-Operated Switch – SZ 4315.520

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Door-Operated Switch – SZ 4315.520

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Version: With connection cable

Product features

Dimensions: Length: 600 mm (24 ")

Rated operating voltage: 400 V

Installation options: for standard and courtesy lights without an integrated door-operated switch

For rated current (max.): 240 V AC, 6 A

Equipment (electrical): Cable color: Orange

Rated insulation voltage: 400 V AC

Rated impulse withstand voltage, phase to phase: 6000 V AC

Packaging unit: 1 pc(s).

Weight/packaging unit: 0.12 kg (0.3 lb.)

EAN: 4028177581357

Customs tariff 85365080

| | |
|------------------------------------|--|
| number: | |
| ETIM 6.0: | EC002626 |
| ETIM 5.0: | EC002626 |
| eCl@ss 8.0/8.1: | 27189266 |
| eCl@ss 7.0/7.1: | 27119116 |
| eCl@ss 6.0/6.1: | 27119116 |
| eCl@ss 5.1/5.1.4: | 27189241 |
| Product description (long): | SZ Door-operated switch, with connection wire, L: 600 mm, orange |
| Approvals | |
| Certificates: | EAC |
| Declarations: | Declaration of conformity |