

Rittal – The System.

Faster – better – everywhere.

Door-Operated Switch – SZ 4315.720

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Door-Operated Switch – SZ 4315.720

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Version: With connection cable

Product features

Dimensions: Length: 600 mm (24 ")

Rated operating voltage: 400 V

Installation options: for compact lights

For rated current (max.): 240 V AC, 2,5 A

Equipment (electrical): Cable color: Gray

Rated insulation voltage: 400 V AC

Rated impulse withstand voltage, phase to phase: 6000 V AC

Packaging unit: 1 pc(s).

Weight/packaging unit: 0.12 kg (0.3 lb.)

EAN: 4028177581388

Customs tariff 85444290

number:	
ETIM 6.0:	EC002626
ETIM 5.0:	EC002626
eCl@ss 8.0/8.1:	27189266
eCl@ss 7.0/7.1:	27119116
eCl@ss 6.0/6.1:	27119116
eCl@ss 5.1/5.1.4:	27189241
Product description (long):	SZ Door-operated switch, with connection wire for compact light, L: 600 mm, grey, UL
Approvals	
Approvals:	CSA UR
Certificates:	EAC
Declarations:	Declaration of conformity