

# Rittal – The System.

Faster – better – everywhere.

## ► Operating housing with handle strips – CP 6315.200

Date : May 29, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Operating housing with handle strips – CP 6315.200

created: 29.05.2018 build on [www.rittal.com/us-en](http://www.rittal.com/us-en)



## Product description

<b>Material:</b>	Housing and door: Carbon steel Handle strips: Aluminum Front panel: Aluminum Cover caps: Plastic
<b>Surface finish:</b>	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Handle strip: Natural anodized Front panel: Natural anodized.
<b>Color:</b>	Housing and door: RAL 7035 Handle strip: Natural anodized Front panel: Natural anodized. Cover caps: Similar to RAL 7024
<b>Protection category IP to IEC 60 529:</b>	IP 55
<b>Supply includes:</b>	Housing with cut-out and reinforcement for support arm connection Ø 130 mm Front with maximum cut-out, covered with easily machinable 3 mm aluminum front panel Side handle strips and cover caps Cam lock with 3 mm double-bit insert Integral interior mounting bracket with TS system punchings
<b>Note:</b>	The support arm connection and door catch may be swapped over by rotating the enclosure Optional: Support arm connection Ø 130 mm, preformed off-center in the reinforcement plate, easily drilled out Lock systems for servicing access from the front: 41 mm lock inserts, type C, lock cylinder, plastic handles and T-handles, type C
<b>Servicing access version:</b>	From the front
<b>Note on Model No.::</b>	Compatible mounting plate 5050.430 with shipping bag 5050.507

## Product features

**Dimensions:** Height: 300 mm (12 ")  
Width: 380 mm (15 ")  
Depth: 210 mm (8.3 ")

**Lock version:** Sickle-shaped locking nose

**No. of locks:** 1

**Lock Insert:** 3 mm double-bit

**Packaging unit:** 1 pc(s).

**Weight/packaging unit:** 7.5 kg (16.5 lb.)

**EAN:** 4028177693944

**Customs tariff number:** 94032080

**ETIM 6.0:** EC002504

**ETIM 5.0:** EC002504

**eCl@ss 8.0/8.1:** 27180505

**eCl@ss 7.0/7.1:** 27180505

**eCl@ss 6.0/6.1:** 27180505

**eCl@ss 5.1/5.1.4:** 27180505

**Product description (long):** CP Operating housing with handle strips, WHD: 380x300x210 mm, Sheet steel, handle strips made of aluminum, Servicing access from the front

## Approvals

**Approvals:** CSA  
TÜV

**Declarations:** Declaration of conformity