

# Rittal – The System.

Faster – better – everywhere.

## ► Operating housing with handle strips – CP 6315.600

Date : May 29, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Operating housing with handle strips – CP 6315.600

created: 29.05.2018 build on [www.rittal.com/us-en](http://www.rittal.com/us-en)



## Product description

<b>Material:</b>	Housing and door: Carbon steel Handle strips: Aluminum Front panel: Aluminum Cover caps: Plastic
<b>Surface finish:</b>	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Handle strip: Natural anodized Front panel: Natural anodized.
<b>Color:</b>	Housing and door: RAL 7035 Handle strip: Natural anodized Front panel: Natural anodized. Cover caps: Similar to RAL 7024
<b>Protection category IP to IEC 60 529:</b>	IP 55
<b>Supply includes:</b>	Housing with cut-out and reinforcement for support arm connection Ø 130 mm Front with maximum cut-out, covered with easily machinable 3 mm aluminum front panel Side handle strips and cover caps Cam lock with 3 mm double-bit insert Integral interior mounting bracket with TS system punchings
<b>Note:</b>	The support arm connection and door catch may be swapped over by rotating the enclosure Optional: Support arm connection Ø 130 mm, preformed off-center in the reinforcement plate, easily drilled out Lock systems for servicing access from the front: 41 mm lock inserts, type C, lock cylinder, plastic handles and T-handles, type C
<b>Servicing access version:</b>	From the front
<b>Note on Model No.::</b>	Compatible mounting plate 5050.442 with shipping bag 5050.507

## Product features

<b>Dimensions:</b>	Height: 600 mm (24 ") Width: 600 mm (24 ") Depth: 210 mm (8.3 ")
<b>Lock version:</b>	Sickle-shaped locking nose
<b>No. of locks:</b>	2
<b>Lock Insert:</b>	3 mm double-bit
<b>Packaging unit:</b>	1 pc(s).
<b>Weight/packaging unit:</b>	22.8 kg (50.3 lb.)
<b>EAN:</b>	4028177698314
<b>Customs tariff number:</b>	94032080
<b>ETIM 6.0:</b>	EC002504
<b>ETIM 5.0:</b>	EC002504
<b>eCl@ss 8.0/8.1:</b>	27180505
<b>eCl@ss 7.0/7.1:</b>	27180505
<b>eCl@ss 6.0/6.1:</b>	27180505
<b>eCl@ss 5.1/5.1.4:</b>	27180505
<b>Product description (long):</b>	CP Operating housing with handle strips, WHD: 600x600x210 mm, Sheet steel, handle strips made of aluminum, Servicing access from the front

## Approvals

<b>Approvals:</b>	CSA TÜV
<b>Declarations:</b>	Declaration of conformity