

Rittal – The System.

Faster – better – everywhere.

► **Wall-mounted enclosures EL, 3-part pre-configured with mounting angles, depth-variable – DK 7715.535**

Date : May 25, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wall-mounted enclosures EL, 3-part pre-configured with mounting angles, depth-variable – DK 7715.535

created: 25.05.2018 build on www.rittal.com/us-en



Product description

Version: Pre-configured

Description: Wall-mounted enclosure with hinged door provides optimum accessibility.

Material: Wall and hinged part: Carbon steel, 1.5 mm
Viewing window: Single-pane safety glass, 3 mm

Surface finish: Powder-coated

Color: Wall and hinged part: RAL 7035
Viewing door: RAL 7035/7015 (slate gray)

**Protection category
IP to IEC 60 529:** IP 54 in conjunction with solid gland plate, top and bottom

Supply includes: Wall section closed at top and bottom with flange plate, two vertical mounting rails and horizontal C-profile rails for cable clamping
Hinged part with 25 mm pitch pattern in the front and rear frame, two 482.6 mm (19") profile angles at the front, fully depth adjustable and side outlet filters on left and right
Ground rail with star grounding
Designer viewing door
1 enclosure key double bit no. 5
Wall mounting brackets, 10 mm, reinforced
Mini-comfort handle
Security lock 3524 E

Base material: Carbon steel

Product features

Dimensions:	Height: 746 mm (29 ") Height units: 15 U (15 U) Width: 600 mm (24 ") Depth: 673 mm (26 ")
Depth hinged part:	516 mm (20 ")
Installation depth:	620 mm (24 ")
Clearances:	Clearance height: 683 mm (27 ") Clearance width: 502 mm (20 ")
Wall section:	Depth: 135 mm (5.3 ")
Load capacity:	Hinged part, static (max.): 750 N (750 N)
Packaging unit:	1 pc(s).
Weight/packaging unit:	48 kg (105.8 lb.)
EAN:	4028177551022
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC002500
eCl@ss 8.0/8.1:	27142408
eCl@ss 7.0/7.1:	27180208
eCl@ss 6.0/6.1:	27180208
eCl@ss 5.1/5.1.4:	27180204
Product description (long):	DK Wall-mounted enclosures, 3-part, WHD: 600x746x673 mm, 15 U, Pre-configured, with mounting angles, depth-variable
Approvals	
Approvals:	UL + C-UL
Certificates:	Protection category
Declarations:	Declaration of conformity