

Rittal – The System.

Faster – better – everywhere.

► Profile rails, 482.6 mm (19") for TS – DK 7827.221

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Profile rails, 482.6 mm (19") for TS – DK 7827.221

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Version:	L-shaped mounting angle
Benefits:	Integral U markings in the front facilitate systematic assembly within the 19" level. L rails accommodate the installation kits of server systems Suitable for 19" partial expansion
Material:	Carbon steel, 2 mm
Technical specifications:	Integral 482.6 mm (19") punchings (EIA standard) Side round and square punchings Clear chromated for conductive connection of 19" fixtures
Supply includes:	Assembly components

Product features

Suitable for:	Enclosure type: TS Height: 2200 mm (87 ")
Dimensions:	Width: 19"
Height units:	47 U
Packaging unit:	2 pc(s).
Weight/packaging unit:	5.22 kg (11.5 lb.)
EAN:	4028177234987

Customs tariff number:	73269098
ETIM 6.0:	EC002620
ETIM 5.0:	EC002620
eCl@ss 8.0/8.1:	27189261
eCl@ss 7.0/7.1:	27189261
eCl@ss 6.0/6.1:	27189261
eCl@ss 5.1/5.1.4:	27182504
Product description (long):	DK-TS Mounting angles, 482.6 mm (19"), L-shaped mounting angle, For H: 2200 mm, 47 U