

Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure for Disconnect – WM 8017.589

Date : May 29, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wallmounted enclosure for Disconnect – WM 8017.589 - WM483812XC

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Description:	These flange mount disconnect wallmount enclosures can be used for virtually any application. The WM series ensures NEMA protection through a secure locking system, foamed-in-place gasket, and knife-edge sealing surface. Features include a cold rolled steel body and door, and a zinc plated mounting panel.
Material:	Door: Carbon steel, 2.0 mm, all-round foamed-in PU seal Housing: Carbon steel Mounting plate: Carbon steel, zinc-plated
Surface finish:	Dipcoat-primed and powder-coated, textured paint
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Supply includes:	Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes Flange door with universal disconnect cutout 3-point latching L-Handle

Product features

Dimensions:	Height: 1200 mm (47 ") Width: 975 mm (38 ")
-------------	--

Depth: 300 mm (12 ")

Material thickness::	Housing: 2 mm (0.08 ") Door: 2 mm (0.08 ") Mounting plate: 3 mm (0.12 ")
-----------------------------	--

Mounting plate:	Height: 1155 mm (45 ") Width: 840 mm (33 ")
------------------------	--

Packaging unit:	1 pc(s).
------------------------	----------

Weight/packaging unit:	89 kg (196.2 lb.)
-------------------------------	-------------------

EAN:	83166
-------------	-------

Approvals

Approvals:	UL + C-UL
-------------------	-----------