

# Rittal – The System.

Faster – better – everywhere.

## **Wallmounted enclosure for Disconnect – WM 8017.592**

Date : May 29, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Wallmounted enclosure for Disconnect – WM 8017.592 - WM603812XC

created: 29.05.2018 build on [www.rittal.com/us-en](http://www.rittal.com/us-en)



## Product description

<b>Description:</b>	These flange mount disconnect wallmount enclosures can be used for virtually any application. The WM series ensures NEMA protection through a secure locking system, foamed-in-place gasket, and knife-edge sealing surface. Features include a cold rolled steel body and door, and a zinc plated mounting panel.
<b>Material:</b>	Door: Carbon steel, 2.0 mm, all-round foamed-in PU seal Housing: Carbon steel Mounting plate: Carbon steel, zinc-plated
<b>Surface finish:</b>	Dipcoat-primed and powder-coated, textured paint
<b>Color:</b>	RAL 7035
<b>Protection category IP to IEC 60 529:</b>	IP 66
<b>Protection category NEMA:</b>	NEMA 4
<b>Supply includes:</b>	Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes Flange door with universal disconnect cutout

## Product features

<b>Dimensions:</b>	Height: 1500 mm (59 ") Width: 975 mm (38 ") Depth: 300 mm (12 ")
--------------------	--

<b>Material thickness:</b>	Housing: 2 mm (0.08 ") Door: 2 mm (0.08 ") Mounting plate: 3 mm (0.12 ")
<b>Mounting plate:</b>	Height: 1455 mm (57 ") Width: 840 mm (33 ")
<b>Packaging unit:</b>	1 Pair
<b>Weight/packaging unit:</b>	107 g (3.8 oz)
<b>EAN:</b>	83169
<b>Approvals</b>	
<b>Approvals:</b>	UL + C-UL