Rittal - The System.

Faster – better – everywhere.

Wallmountedenclosure Stainlesssteel – WM 8017.616

Date: May 24, 2018



ENCLOSURES >> POWER DISTRIBUTION >> CLIMATE CONTROL >> IT INFRASTRUCTURE >> SOFTWARE & SERVICES >>

Wallmounted enclosure Stainless steel – WM 8017.616 - WM202006N4

created: 24.05.2018 build on www.rittal.com/us-en



Prod	luct	aah	crin	tion
riuu	uci	ues	CHID	เมษา

Material: Door: Stainless steel, all-round foamed-in PU seal

Housing and door: Stainless steel 1.4301 (AISI 304)

Mounting plate: Carbon steel, zinc-plated

Surface finish: Brushed

Protection category IP to IEC 60 529:

IP 66

Protection category

NEMA:

NEMA 4X

Supply includes:

Housing with door(s) Left hand hinge Mounting plate

Wall mounting blind-nuts

Product features

Dimensions: Height: 500 mm (20 ")

Width: 500 mm (20 ") Depth: 150 mm (5.9 ")

Material thickness:: Housing: 1.5 mm (0.06 ")

Door: 1.5 mm (0.06 ")

Mounting plate: 2.5 mm (0.1 ")

Mounting plate: Height: 470 mm (19 ")

Width: 449 mm (18 ")

© Rittal 2018

1

Lock version:	Quarter turn
Packaging unit:	1 pc(s).
Weight/packaging unit:	17 kg (37.5 lb.)
EAN:	83192
Approvals	
Approvals:	UL + C-UL

© Rittal 2018