Rittal – The System.

Faster – better – everywhere.

Baying systems TS 8 Single – TS 8085.500



ENCLOSURES

POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Baying systems TS 8 Single – TS 8085.500 created: 29.05.2018 build on www.rittal.com/us-en



Product description

| Material: | Enclosure frame: Carbon steel, 1.5 mm |
|--|---|
| | Roof: Carbon steel, 1.5 mm |
| | Door: Carbon steel, 2.0 mm |
| | Rear wall: carbon steel, 1.5 mm |
| | Base plates: Carbon steel, 1.5 mm |
| | Mounting plate: Carbon steel, 3.0 mm |
| | |
| Surface finish: | Enclosure frame: Dipcoat-primed |
| | Door, roof and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint |
| | Mounting plate and base plates: Zinc-plated |
| Color: | RAL 7035 |
| Protection category IP to IEC 60 529: | IP 55 |
| | |
| Protection category NEMA: | NEMA 12 |
| Supply includes: | Enclosure frame with door |
| | Roof plate |
| | Rear panel, detachable |
| | 4 eyebolts |
| | Lock: 3 mm double-bit |
| | Base Plates |
| | Mounting plate |
| | |
| Product features | |
| Dimensions: | Height: 1800 mm (71 ″) |
| | Width: 1000 mm (39 ") |
| | Depth: 500 mm (20 [~]) |

| Number of doors: | 1 |
|---------------------------|---|
| Packaging unit: | 1 pc(s). |
| Weight/packaging unit: | 156.8 kg (345.7 lb.) |
| EAN: | 81071 |
| Approvals | |
| Approvals: | Bureau Veritas CSA DNV-GL Russian Maritime Register of Shipping TÜV UL + C-UL |