

Rittal – The System.

Faster – better – everywhere.

Flat Copper Busbar Supports – SV 9340.050

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Flat Copper Busbar Supports – SV 9340.050

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Material:	Polyamide (PA 6.6) Fire protection corresponding to UL 94-V0
Color:	RAL 7035
Note:	The use of a base tray is required for UL applications. UL approval only applies in conjunction with AC application

Product features

Suitable for busbars:	With dimensions (mm): 15 x 5 - 30 x 10
Number of poles:	3-pole
Center-to-center spacing of busbars:	60 mm
Rated operating voltage:	1000 V, 3~ 1500 V (DC)
With internal attachment:	yes
Packaging unit:	4 pc(s).
Weight/packaging unit:	0.7 kg (1.5 lb.)
EAN:	4028177525573

Customs tariff number:	85469010
ETIM 6.0:	EC001166
ETIM 5.0:	EC001166
eCl@ss 8.0/8.1:	27400607
eCl@ss 7.0/7.1:	27400607
eCl@ss 6.0/6.1:	27400607
eCl@ss 5.1/5.1.4:	27370302
Product description (long):	SV Busbar support, 3-pole, 60 mm bar centre distance, for busbar WH: 15x5-30x10 mm, UL design
Approvals	
Approvals:	ABS C-UL DNV-GL Lloyds Register of Shipping UL + C-UL
Certificates:	EAC
Declarations:	Declaration of conformity