

Rittal – The System.

Faster – better – everywhere.

OM adapter with Connection Cables – SV 9340.430

Date : May 25, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



OM adapter with Connection Cables – SV 9340.430

created: 25.05.2018 build on www.rittal.com/us-en



Product description

Material: Polyamide (PA 6.6)
Fire protection corresponding to UL 94-V0

Color: Chassis: RAL 7035

Note: The technical data may vary for UL applications.

Product features

Suitable for busbars: with cross-section height: 5 mm
with cross-section height: 10 mm

Number of poles: 3-pole

For bar systems with center-to-center spacing: 60 mm

Dimensions: Height: 208 mm (8.2 ")
Width: 55 mm (2.2 ")

Rated operating voltage: 690 V, 3~

Connection cable: Cross-section: AWG 6
Length: 130 mm (5.1 ")

Support Frame: Height: 170 mm (6.7 ")
Width: 55 mm (2.2 ")

| | |
|------------------------------------|---|
| Rated current (max.): | 65 A |
| Number of support rails: | 1 |
| Height of support rails: | 10 mm (0.39 ") |
| Support rail type: | TS 55E |
| Packaging unit: | 1 pc(s). |
| Weight/packaging unit: | 0.38 kg (0.8 lb.) |
| EAN: | 4028177502543 |
| Customs tariff number: | 85369095 |
| ETIM 6.0: | EC001531 |
| ETIM 5.0: | EC001531 |
| eCl@ss 8.0/8.1: | 27370304 |
| eCl@ss 7.0/7.1: | 27370304 |
| eCl@ss 6.0/6.1: | 27370304 |
| eCl@ss 5.1/5.1.4: | 27370302 |
| Product description (long): | SV OM adaptor, 65 A, 690 V, 3-pole, connection cable AWG 6, WH: 55x208 mm, support frame, support rail TS 55E |

Approvals

| | |
|----------------------|---|
| Approvals: | ABS C-UL DNV-GL Lloyds Register of Shipping UL + C-UL |
| Certificates: | EAC |
| Declarations: | Declaration of conformity |