Rittal - The System.

Faster – better – everywhere.

PLS Busbar Supports– SV 9342.050

Date: May 29, 2018



NCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

PLS Busbar Supports – SV 9342.050

created: 29.05.2018 build on www.rittal.com/us-en



Droduct	description
riouuci	description

Material: Polyamide (PA 6.6)

Fire protection corresponding to UL 94-V0

Color: RAL 7035

Note: The use of a base tray is required for UL applications.

UL approval only applies in conjunction with AC application

Product features

Suitable for busbars: Type: PLS 1600

Number of poles: 3-pole

Center-to-center spacing of busbars:

60 mm

Rated operating voltage:

1000 V, 3~ 1500 V (DC)

With internal attachment:

yes

Top-mounting: yes

Packaging unit: 4 pc(s).

Weight/packaging unit:

0.59 kg (1.3 lb.)

© Rittal 2018

EAN:	4028177525641
Customs tariff number:	85469010
ETIM 6.0:	EC001166
ETIM 5.0:	EC001166
eCl@ss 8.0/8.1:	27400607
eCl@ss 7.0/7.1:	27400607
eCl@ss 6.0/6.1:	27400607
eCl@ss 5.1/5.1.4:	27370302
Product description (long):	SV Busbar support, PLS 1600, 3-pole, 60 mm bar centre distance, UL design
Approvals	
Approvals:	ABS C-UL UL + C-UL
Certificates:	EAC
Declarations:	Declaration of conformity

© Rittal 2018