

Rittal – The System.

Faster – better – everywhere.

Circuit-Breaker Component Adaptors 3-pole – SV 9342.550

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Circuit-Breaker Component Adaptors 3-pole – SV 9342.550

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Material: Polyamide (PA 6.6)
Fire protection corresponding to UL 94-V0

Color: RAL 7035

Supply includes: Terminal cover
Sliding Blocks

Note: Cable outlet: Switch outlet or as outgoing cable from the switchgear
The technical data may vary for UL applications.

Product features

Suitable for busbars: with cross-section height: 5 mm
with cross-section height: 10 mm

Number of poles: 3-pole

For bar systems with center-to-center spacing: 60 mm

Dimensions: Height: 225 mm (8.9 ")
Width: 90 mm (3.5 ")

Type of connection (electrical): Box terminal

Rated operating 690 V, 3~

voltage:	
Clamping area for laminated copper bars:	Height: 15.5 mm (0.61 ") Width: 18.5 mm (0.73 ")
Connection for round conductor cross-sections:	35 mm ² - 120 mm ²
Rated current (max.):	125 A
Cable outlet:	Bottom
To fit manufacturer (model):	ABB (S1, S2, T1, T1 UL, T2, T2 UL, XT1, XT2) Allen Bradley (140-CMN) Eaton (NZM1, NZM1 UL, BZM B1) GE (FD160) OEZ (BC160N) Schneider Electric (NS80, NSC100, NSE75, NS100) Schrack (MC1) Siemens (3RV13 53, 3VT1, 3VA10, 3VA11, 3VA51) Terasaki (E125, S125)
Packaging unit:	1 pc(s).
Weight/packaging unit:	0.82 kg (1.8 lb.)
EAN:	4028177525665
Customs tariff number:	85369095
ETIM 6.0:	EC001531
ETIM 5.0:	EC001531
eCl@ss 8.0/8.1:	27370304
eCl@ss 7.0/7.1:	27400613
eCl@ss 6.0/6.1:	27400613
eCl@ss 5.1/5.1.4:	27370302
Product description (long):	SV Circuit-breaker component adaptor, 125 A, 690 V, 3-pole, cable outlet bottom, round conductor connection 35-120 mm ² , clamping area WH: 18,5x15,5 mm

Approvals

Approvals:	ABS C-UL DNV-GL UL + C-UL
-------------------	------------------------------------

Certificates:

EAC

Declarations:

Declaration of conformity
