

Rittal – The System.

Faster – better – everywhere.

➤ PK Polycarbonate Housings without knockouts – PK 9508.000

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



PK Polycarbonate Housings without knockouts – PK 9508.000

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Applications:	Ambient temperature range: -35°C...+80°C The specified temperatures can be limited by the installed equipment
Material:	Housing: Fiber-glass reinforced polycarbonate Cover gray: Fiberglass-reinforced polycarbonate, all-round foamed PU seal Cover screws: Polyamide Insulating bungs: Polythene
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4X
Supply includes:	Housing with cover Cover screws Insulating bungs for wall mounting screws
Base material:	Polycarbonate

Product features

Dimensions:	Height: 94 mm (3.7 ") Width: 130 mm (5.1 ") Depth: 57 mm (2.2 ")
Cover:	gray

Ambient temperature range:	-35°C...+80°C
Packaging unit:	4 pc(s).
Weight/packaging unit:	0.9 kg (2 lb.)
EAN:	4028177139251
Customs tariff number:	94037000
ETIM 6.0:	EC000261
ETIM 5.0:	EC002600
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180102
Product description (long):	PK Polycarbonate enclosure, WHD: 130x94x57 mm, fibreglass-reinforced polycarbonate, without knockouts, with grey cover
Approvals	
Approvals:	Bureau Veritas C-UL UL UL + C-UL
Declarations:	Declaration of conformity